



## SSH-158-3

**SnapStak® Hanger for 1-5/8 in coaxial cable, triple stack capability, includes reinforcement bar**

### Dimensions

Nominal Size	1-5/8 in
Compatible Diameter, maximum	52.070 mm   2.050 in
Compatible Diameter, minimum	48.260 mm   1.900 in
Height	41.00 mm   1.61 in
Length	90.00 mm   3.54 in
Width	50.90 mm   2.00 in

### Electrical Specifications

DTF Effect	0.1 dB
Return Loss Effect	0.1 dB

### General Specifications

Hanger Type	Snap-in hanger
Cables Per Hanger	1
Color	Silver
Material Type	Stainless steel
Maximum Stack Height	3
Package Quantity	10

### Mechanical Specifications

Axial Load Capability, minimum with no cable slippage	≥5 times cable weight
Corrosion Resistance, minimum with no degradation	≥500 hours in salt spray chamber
Mounting	3/4 in drilled cable ladder
Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Vibration Survival	≥4 hours at resonant frequency

### Packed Dimensions

Height	22.0 cm   8.7 in
Length	14.4 cm   5.7 in
Shipping Weight	0.60 kg   1.32 lb
Width	15.0 cm   5.9 in

### Regulatory Compliance/Certifications

Agency	Classification
ISO 9001:2008	Designed, manufactured and/or distributed under this quality management system