

Fuse plug - ST-SILED 24-UK 4 - 0921037

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, nominal current: 6.3 A, length: 33.1 mm, width: 6.1 mm, height: 45.7 mm, color: black

The figure shows the version without LED/light indicator

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 010294
GTIN	4017918010294
Weight per Piece (excluding packing)	5.880 g
Custom tariff number	85369095
Country of origin	Poland

Technical data

General

Note	If the fuse is defective, the downstream circuit is not off load
Color	black
Insulating material	PA
Flammability rating according to UL 94	V2
Maximum power dissipation for nominal condition	1.5 W

Dimensions

Width	6.1 mm
Length	33.1 mm

General

Fuse plug - ST-SILED 24-UK 4 - 0921037

Technical data

General

Fuse	G / 5 x 20
Insulating material group	CTI 600
LED voltage range	15 V AC/DC ... 30 V AC/DC
LED current range	3.5 mA ... 7.5 mA
Nominal current I_N	6.3 A
Nominal voltage U_N	24 V
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	125 °C
Static insulating material application in cold	-60 °C
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed
Calorimetric heat release NFPA 130 (ASTM E 1354)	27,5 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3

Connection data

Connection method	Plug connection
-------------------	-----------------

Standards and Regulations

Connection in acc. with standard	CSA
Flammability rating according to UL 94	V2

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values