



IPL250-3 SHOWN

| PART NUMBER | NO. OF PORTS | LENGTH |
|-------------|--------------|--------|
| IPL250-3 | 3 | 2.93 |
| IPL250-4 | 4 | 3.80 |
| IPL250-5 | 5 | 4.66 |
| IPL250-6 | 6 | 5.22 |
| IPL250-8 | 8 | 7.24 |
| IPL250-10 | 10 | 8.97 |

WIRE ENTRY PORT
WIRE RANGE: 250KCMIL - #6 AWG
PRE-FILLED W/ OXIDE INHIBITOR

CONTACT NSi FOR SALES @ 800.321.5847

NOTES:

1. CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
2. UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
3. DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
4. COLD TEMPERATURE RATED TO -45°C.
5. HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

| | | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------------------------------------------|---------------|
| | | POLARIS SALES CO. INC | |
| | | 11625 PROSPEROUS DRIVE ODESSA, FL 33556 | |
| PROPRIETARY AND CONFIDENTIAL | | TITLE: INSULATED 250 CONNECTOR | |
| THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED. | | DWG. NO. IPL250- | |
| DRAWN BY S.PARRY | NAME S.PARRY | DATE 06/2012 | MATERIAL: N/A |
| SCALE: N/A | | SHEET: 1 OF 1 | |