
AL3300™ SERIES RACEWAY


AL3300 Series Raceway Ordering Information (continued)

AL3310B Blank End Fitting




Closes off open end of AL3300 Series Raceway.

AL3318 External Elbow




For making external corners. Two AL3301 Couplings included.

AL3310B1 End Fitting




End feeds raceway with 1/2" or 3/4" trade size conduit or armored cable.

AL3346D Duplex Receptacle Cover




Mounts standard duplex devices to cover. Can also be used with 106 communication frames.

AL3311 90° Flat Elbow




Right angle turns on same surface. Two AL3301Couplings included.

AL3346DO Offset Duplex Receptacle Cover Plate (For Divided Raceway)




Installs duplex devices in divided aluminum raceway. 6" (152mm) offset divider included. Can also be used with 106 communication frames. Provided with offset divider.

AL3315 Tee




90° tee connection of two runs of AL3300 Series Raceway. Three AL3301Couplings included.

AL3346E Single Receptacle Cover Plate (1.40" diameter)




Installs straight blade and locking single receptacles with face diameters of 1.38"-1.39" (35mm-36mm).

AL3316 Cross Fitting




90° cross-through connection of two runs of raceway. Four AL3301Couplings included.

AL3317 Internal Elbow



For making 90° internal corners. Two AL3301 Couplings included.

AL3346G Rectangular Device Cover Plate




Installs rectangular devices including surge receptacles, GFCI, and other rectangular faced single-gang wiring devices. Can also be used with decorator style communication frames.

AL3300 SERIES RACEWAY

Ordering Information





AL3300 Series Raceway's low profile, divided aluminum raceway meets the demands of today's laboratories, healthcare facilities and upscale office locations, providing a compact and effective method of consolidating power and communication cabling.

Material: 6063 T6 Aluminum Alloy Wall Thickness: 0.078" (1.99mm)


Anodized Finish Thickness: 0.004" (0.004mm)

AL3300WC Wire Clip




For holding wires and cables in raceway base. Use with undivided raceway, snap into grooves of base.

AL3309 Ground Clamp




For connection of equipment grounding conductor to provide additional ground to raceway.

AL3301 Coupling




Set screw coupling used for attaching in-line raceway sections.

AL3310B Blank End



For closing open end of AL3300 Series Raceway.

AL3301D Divider Clip



Required for holding AL3300D5 divider in place. Use one every 30" (76.2m).

AL3310B1 End



For end feeding raceway with 1/2" (12.7mm) or 3/4" (19.1mm) trade size conduit or armored cable.