




Color :  White

UPC Code : 078477996119

Country Of Origin : China



Available Colors :



Black



Light Almond

GUAC2-W

20A SmartlockPro® Self-Test GFCI Combination 24W(4.8A) Type A/C USB In-Wall Charger Outlet – White

20 Amp, 125 Volt Receptacle/Outlet, 20 Amp Feed-Through, Tamper-Resistant, Self-Test SmartlockPro® Self-Test GFCI Combination Type A/C USB In-Wall Charger, Wire Leads, NEMA 5-20R, 24W (4.8 Amps), Type-A/C USB Chargers, screws and self-grounding clip included – White

- SAFE – Delivers continuous ground fault protection, automatically self-tests to ensure it can respond to a ground fault
- FAST CHARGING – Smart chip technology provides over 2X the charging power of other GFCI USB outlets for a faster charge
- CODE REQUIRED – Fulfill NEC® requirements anywhere GFCI protection is needed
- SIMPLE – Status indicator light provides simple, intuitive feedback
- INSTALL – Requires extra deep wallbox for installation

Technical Information

Product Features

Amperage : 20 A

At Rated Voltage : 1 HP

Brand : SmartlockPro

Color : White

Feature : Self-Test

Flammability : UL94, 5VA

Grade : Residential/Commercial Specification Grade

Grounding : Self-Grounding

NEMA : 5-20R

Pole : 2

Product Type : GFCI/Outlet/USB Combo

Tamper Resistant : Yes

Termination : Wire leads (12AWG)

Trip Level : Class A, 5mA plus or minus 1mA

Type : GFCI/USB A/C Combination

Voltage : 125 VAC

Wallplate : Not included

Warranty : 2-Year Limited

Wire : 5

AC Horsepower Ratings

At Rated Voltage : 1 HP

Dielectric Voltage : Withstands 1250VAC per UL 943 and CSA-C22.2 No. 144.1-06

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Electrical Specifications

Grounding : Self-Grounding

Grounding Wire : Green ground wire

Operating Temperature : -10°C to 40°C

Material Specifications

Body Material : Thermoplastic

Color : White

Cover Material : Thermoplastic

Face Material : Thermoplastic

Grade : Residential/Commercial Specification Grade

Line Contacts : Brass Double Wipe .031 Thick

Notes : Wallplate not included

Product ID : Ratings are permanently marked on device

Strap Material : Galvanized Steel

Terminal ID : Green lead - GND. Line and load both have: Black lead - Hot, White lead - Neutral

Yoke : Zinc-Plated Steel

Mechanical Specifications

Pole : 2

Tamper Resistant : Yes

Trip Level : Class A, 5mA plus or minus 1mA

Type : GFCI/USB A/C Combination

Voltage : 125 VAC

Wire : 5

Standards & Certifications

ANSI : Yes

CSA C22.2 No. 42 : Yes

CSA-C22.2 No. 144.1-06 : Yes

FCC Part 15 : Class B

Operating Temperature : -10°C to 40°C

Ratings : 15A - 125V, 4.8A @ 5V

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Voltage : 125 VAC

Environmental Specifications

Flammability : UL94, 5VA

Fed Spec WC-596 : No

Listed : cCSAus

NOM : Yes

UL 1310 : Yes

UL 498 : Yes

Patents*

CA2427366	US10483066
CA2515035	US7355117
CA2621644	US7697252
CA2624409	US7737809
CA2677283	US7820909
CA2730014	US7868719
MX251584	US8004804
MX269232	US8242362
MX276626	US8587914
MX302458	US9053886
MX308495	US9276393
MX344697	

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):

+1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-

1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts/

