

Rittal – The System.

Faster – better – everywhere.

Wallmounted enclosure – WM 1034.250

Date : Jan 21, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Wallmounted enclosure – WM 1034.250 - WM161208NC

created: 21.01.2017 build on www.rittal.com/us-en



Product description

Material:	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
Surface finish:	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
Color:	RAL 7035
Protection category IP to IEC 60 529:	IP 66
Protection category NEMA:	NEMA 4
Supply includes:	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes Quarter turn latch with slotted head insert

Product features

Dimensions:	Height: 400 mm (16 ") Width: 300 mm (12 ") Depth: 210 mm (8.3 ")
Material thickness::	Housing: 1.5 mm (0.06 ") Door: 1.5 mm (0.06 ") Mounting plate: 1.5 mm (0.06 ")
Mounting plate:	Height: 375 mm (15 ") Width: 254 mm (10 ")

Packaging unit:	1 pc(s).
Weight/packaging unit:	9 kg (19.8 lb.)
EAN:	83106
Approvals	
Approvals:	UL

2017 © Rittal Corporation