

OT160ET3



Products Low Voltage Products and Systems Switches Switch Disconnectors

General Information

Extended Product Type:	OT160ET3
Product ID:	1SCA022350R1960
EAN:	6417019100456
Catalog Description:	OT160ET3 switch-disconnector
Long Description:	For mounting into the door or side wall. Includes handle OHB65J6, IP 65, and shaft OXP6x1 30, length 130 mm.

Additional Information

ABB Industrial IT Suite:	Control IT
BV Certificate:	1SCC301048D0202
Conventional Free-air Thermal Current (I_{th}):	$q = 40\text{ }^{\circ}\text{C}$ 200 A
Conventional Thermal Current (I_{the}):	Fully Enclosed 160 A
Country of Origin:	Finland (FI)
Customs Tariff Number:	85365080
DNV Certificate:	1SCC301051D0201
Data Sheet, Technical Information:	1SCC301013M0003
Declaration of Conformity - CE:	1SCC301012D0201
E-nummer:	3171148
EAN:	6417019100456
ETIM 5:	EC000216 - Switch disconnector
ETIM 6:	EC000216 - Switch disconnector
Environmental Information:	1SCC301009D0201
GL Certificate:	1SCC301042D0201
IIT Publishing Status:	Level 0 - Information enabled
Industrial IT Certification Level:	0
Instructions and Manuals:	1SCC301013M0004
Invoice Description:	OT160ET3 switch-disconnector
KEMA Certificate:	1SCC301084D0201
LR Certificate:	1SCC301039D0202
Minimum Order Quantity:	1 piece
Number of Poles:	3
Object Classification Code:	Q
Switches Operating Mechanism:	Mechanism Between the Poles
Package Level 1 EAN:	6417019100456
Package Level 1 Gross Weight:	1.40 kg
Package Level 1 Height:	133 mm
Package Level 1 Length:	209 mm
Package Level 1 Units:	1 piece
Package Level 1 Width:	181 mm
Position of Line Terminals:	Top In - Bottom Out Bottom In - Top Out
Power Loss:	at Rated Operating Conditions per Pole 6.5 W
Product Main Type:	OT160
Product Name:	Switch-disconnector
Product Net Depth:	90 mm

Product Net Depth:	90 mm
Product Net Height:	131 mm
Product Net Weight:	1.40 kg
Product Net Width:	127 mm
Rated Operational Current AC-21A (I_b):	(500 V) 160 A (690 V) 160 A (380 ... 415 V) 160 A
Rated Operational Current AC-22A (I_b):	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-23A (I_b):	(500 V) 125 A (690 V) 80 A (380 ... 415 V) 135 A
Rated Operational Power AC-23A (P_b):	(220 ... 240 V) 45 kW (400 V) 75 kW (415 V) 75 kW (500 V) 75 kW (690 V) 75 kW
RoHS Information:	1SCC301148D0201
Selling Unit of Measure:	piece
Short Description:	Switch-disconnector 200A. Door mounted, 3-pole
Standards:	IEC

