

INHIBITORS

Oxide Inhibitor & Duct Sealing Compound OX, DS SERIES



OXIDE INHIBITOR

- Universal oxide inhibitor for aluminum and/or copper terminations.
- Remains stable over a wide temperature range.
- Supplied in clear, easy-squeeze bottles or tubes.



CAT. NO.	FIG. NO.	DESCRIPTION	SIZE (OZ)	STD. CTN. QTY.
OX-8	1	Oxide Inhibitor. Squeeze Bottle.	8 oz.	12
OX-4	2	Oxide Inhibitor. Squeeze Bottle.	4 oz.	12
OX-1	3	Oxide Inhibitor. Squeeze Tube.	3/4 oz.	100

DUCT SEALING COMPOUND

- Intended for sealing around electrical service entries, junction boxes and other devices where weather-proofing is critical.
- Will stay soft and pliable for several years and has an excellent shelf life.
- Will not damage wire covers, glass, wood, painted surfaces, plastics or other materials it may contact.
- It is chemically inert, inhibiting no chemical activity and is nontoxic.
- Contains no asbestos or mineral fibers and no mineral oil which can shorten the effective life of the product.
- Remains pliable through a wide range of temperatures and will adhere to most clean dry surfaces.



CAT. NO.	FIG. NO.	DESCRIPTION	STD. CTN. QTY.
DS184	1	Duct Seal – 1 Lb. Pkg.	50
DS185	2	Duct Seal – 5 Lbs. Pkg.	10