SIEMENS

Data sheet US2:45GG10AFA



Contactor, 45DP,40A,1P,Open,120 Contactor, 45DP,40A,1P,Open,120

product brand name	Class 45 DP Contactors	
design of the product	Non-reversing Definite Purpose Contactor	
special product feature	Enclosed body and coil with standard cover	
General technical data		
weight [lb]	0.58 lb	
Height x Width x Depth [in]	3.19 × 1.97 × 2.46 in	
touch protection against electrical shock	Not finger-safe	
ambient temperature [°F]		
during storage	158 °F	
during operation	158 158 °F	
ambient temperature		
 during storage 	75 °C	
during operation	70 70 °C	
country of origin	China	
number of poles for main current circuit	1	
Contactor		
size of contactor	40A	
number of NO contacts for main contacts	1	
operating voltage for main current circuit at AC at 60 Hz maximum	600 V	
mechanical service life (operating cycles) of the main contacts typical	250000	
Auxiliary contact		
number of NC contacts for auxiliary contacts	0	
number of NO contacts for auxiliary contacts	0	
number of NC contacts at contactor for auxiliary contacts	0	
number of NO contacts at contactor for auxiliary contacts	0	
number of total auxiliary contacts maximum	0	
Coil		
control supply voltage		
 at AC at 50 Hz rated value 	110 V	
at AC at 60 Hz rated value	110 120 V	
Enclosure		
degree of protection NEMA rating of the enclosure	Open device (no enclosure)	
Mounting/wiring		
mounting position	vertical	
fastening method	Surface mounting and installation	
type of electrical connection for supply voltage line-side	Box lug	
tightening torque [lbf·in] for supply	25 25 lbf·in	
type of connectable conductor cross-sections at line-side for AWG cables single or multi-stranded	4 AWG	

type of electrical connection for load-side outgoing feeder	Box lug
type of connectable conductor cross-sections for AWG cables for load-side outgoing feeder single or multi-stranded	4 AWG
type of electrical connection of magnet coil	Quick connects
type of electrical connection at contactor for auxiliary contacts	Screw-type terminals
Certificates/ approvals	
certificate of suitability	cRUus, ARI 780 & 790, UL File E14900
Further information	

Industrial Controls - Product Overview (Catalogs, Brochures,...)

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/us/Catalog/product?mlfb=US2:45GG10AFA

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/US/en/ps/US2:45GG10AFA

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:45GG10AFA&lang=en

Certificates/approvals
https://support.industry.siemens.com/cs/US/en/ps/US2:45GG10AFA/certificate

last modified:	5/25/2021 🖸