

TIA-607 Pattern Telecommunications Grounding Busbars



TGB Busbars

Part No.	Bar Size	Material	Plexiglass Cover	No. of 5/16" Hole Sets	No. of 7/16" Hole Sets	Approx. Each Wt. (lbs.)
GBI1426TGB	1/4" x 2" x 6"	Copper	No	2	2	1-1/2
GBIP1426TGB*	1/4" x 2" x 6"	Copper	Yes	2	1	2
TGBI1426TGB	1/4" x 2" x 6"	Electro Tin Plated	No	2	2	1-1/2
TGBIP1426TGB*	1/4" x 2" x 6"	Electro Tin Plated	Yes	2	2	2
GBI14210TGB	1/4" x 2" x 10"	Copper	No	4	3	3
GBIP14210TGB*	1/4" x 2" x 10"	Copper	Yes	4	3	3-1/2
TGBI14210TGB	1/4" x 2" x 10"	Electro Tin Plated	No	4	3	3
TGBIP14210TGB*	1/4" x 2" x 10"	Electro Tin Plated	Yes	4	3	3-1/2
GBI14212TGB	1/4" x 2" x 12"	Copper	No	6	3	4
GBIP14212TGB*	1/4" x 2" x 12"	Copper	Yes	6	3	4-1/2
TGBI14212TGB	1/4" x 2" x 12"	Electro Tin Plated	No	6	3	4
TGBIP14212TGB*	1/4" x 2" x 12"	Electro Tin Plated	Yes	6	3	4-1/2

*TGB is standard lettering in black with a minimum lettering height of 3/8". Other sizes available. Please contact factory for more information. See page 61 for plexiglass cover.

- 1/4" thick x 4" wide electrolytic tough pitch copper alloy 110.
- Includes 1-1/2" insulators and 1" offset stainless steel mounting brackets.
- Includes one 1/2 oz. tube of antioxidant (#HCAJ120).
- 5/16" hole sets 5/8" on centers. Accommodates "A" spaced two hole compression lugs.
- 7/16" hole sets 1" on centers. Accommodates "C" spaced two hole compression lugs.
- Other sizes available. Please contact factory for more information.
- Meets Bicsi and TIA-607 standards.