

# Rittal – The System.

Faster – better – everywhere.

## **Wallmounted enclosure – WM 8017.559**

Date : Jan 21, 2017

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# Wallmounted enclosure – WM 8017.559 - WM423608NC

created: 21.01.2017 build on [www.rittal.com/us-en](http://www.rittal.com/us-en)



## Product description

<b>Material:</b>	Door: Carbon steel, all-round foamed-in PU seal Housing: Carbon steel
<b>Surface finish:</b>	Housing and door: Dipcoat primed, powder-coated on the outside, textured paint Mounting plate: Zinc-plated
<b>Color:</b>	RAL 7035
<b>Protection category IP to IEC 60 529:</b>	IP 66
<b>Protection category NEMA:</b>	NEMA 4
<b>Supply includes:</b>	Housing with door(s) Left hand hinge Mounting plate Rear wall mounting holes 3-point latching L-Handle

## Product features

<b>Dimensions:</b>	Height: 1050 mm (41 ") Width: 900 mm (35 ") Depth: 210 mm (8.3 ")
<b>Material thickness::</b>	Housing: 2 mm (0.08 ") Door: 2 mm (0.08 ") Mounting plate: 2.5 mm (0.1 ")
<b>Mounting plate:</b>	Height: 1020 mm (40 ") Width: 840 mm (33 ")

<b>3-point locking system:</b>	yes
<b>Packaging unit:</b>	1 pc(s).
<b>Weight/packaging unit:</b>	71 kg (156.5 lb.)
<b>EAN:</b>	83138
<b>Approvals</b>	
<b>Approvals:</b>	UL

2017 © Rittal Corporation