

Secure-All™

Copper-plated Bracket

Patent # 7,039,965

- Reduce inventory with one bracket that features multiple hole sizes and notches
- Stiffening ribs on top and bottom provide ultimate rigidity
- Heavy gauge copper-plated steel
- All holes and notches are extruded for maximum soldering surface
- Bracketing area on 521-851 is 14" and on 521-852 is 22"
- Heat the tube, not the bracket



521-851



521-852

SUPPLY

DRAINAGE

SUPPORT

Item No.	Dimensions	Holes	Notches	Gauge	Pkg	Min Qty	Case Qty
521-851	2" x 20"	1/2" CTS, 2" O.C. (7) 3/4" CTS, 4" O.C. (3) 1" CTS, 4" O.C. (3)	1/2" CTS, 2" O.C. (7) 3/4" CTS, 2" O.C. (6)	18	B	50	50
521-851PK	2" x 20"	1/2" CTS, 2" O.C. (7) 3/4" CTS, 4" O.C. (3) 1" CTS, 4" O.C. (3)	1/2" CTS, 2" O.C. (7) 3/4" CTS, 2" O.C. (6)	18	C*	25	25
521-852	2 3/8" x 26"	1/2" CTS, 2" O.C. (11) 3/4" CTS, 4" O.C. (5) 1" CTS, 4" O.C. (5)	1/2" CTS, 2" O.C. (11) 3/4" CTS, 2" O.C. (10)	18	B	50	50



Stub Out Bracket

Copper-plated

- Extruded models provide four times the soldering surface for extra strength
- Heat the tube, not the bracket

Galvanized

- For use with Pipe Eye metal stud insulators



521-118



521-810



521-318



521-360

APPENDIX



Related Products


Pipe Eye

p 427



521-3725B

Item No.	Dimensions	Holes	Extruded Holes	Gauge	Pkg	Min Qty	Case Qty
COPPER-PLATED							
521-118	1 1/4" x 20"	1/2" CTS, 2" O.C. (8)		16	B	50	50
521-118R	1 1/4" x 20"	1/2" CTS, 2" O.C. (7)	✓	16	B	25	25
521-126	1 1/4" x 26"	1/2" CTS, 2" O.C. (11)		16	B	50	50
521-810	1 3/4" x 20"	1/2" CTS, 2" O.C. (7) 3/4" CTS, 4" O.C. (4) 1" CTS, 4" O.C. (4)		16	B	50	50
521-810PK	1 3/4" x 20"	1/2" CTS, 2" O.C. (7) 3/4" CTS, 4" O.C. (4) 1" CTS, 4" O.C. (4)		16	C*	50	50
521-820	1 3/4" x 20"	1/2" CTS, 2" O.C. (7) 3/4" CTS, 4" O.C. (4) 1" CTS, 4" O.C. (3)	✓	24	B	50	50
GALVANIZED							
521-318	2" x 20"	1 11/32", 2" O.C. (7)		14	B	50	50
521-360	2" x 26"	1 11/32", 2" O.C. (11)		14	B	50	50
521-3725B	3" x 4 3/4"	1 11/32", 2" O.C. (2)		14	B	100	100



Except Galvanized models