


Viega PureFlow Press transition coupling
Smart Connect technology
Zero Lead

- For transitioning between Viega PureFlow Press and Viega ProPress
- Bronze
- Press connection

Components

EPDM sealing elements

Note

ProPress and PureFlow tool and jaws required

Model 2813PZL

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.076	10	99620	6
1/2	3/4	0.115	10	99626	6
3/4	1/2	0.078	10	99630	6
3/4	3/4	0.115	10	99640	6
1	3/4	0.136	10	99645	6
1	1	0.184	10	99660	6
1 1/4	1	0.236	5	99665	6
1 1/4	1 1/4	0.287	5	99670	6
1 1/2	1	0.276	5	99675	6
1 1/2	1 1/2	0.447	5	99680	6
2	1	0.459	5	99685	6
2	2	0.723	5	99690	6

Reducers


Viega ProPress reducer
Smart Connect technology

- For use with ASTM B88 and B75 tubing
- Copper
- Press connection

Components

EPDM sealing elements

Model 2915.2

P1	P2	Wt [lb]	Quantity	Part No	DG
3/4	1/2	0.126	10	78147	8
1	1/2	0.170	10	15603	8
1	3/4	0.175	10	78152	8
1 1/4	3/4	0.244	1	15593	8
1 1/4	1	0.250	1	78157	8
1 1/2	3/4	0.402	1	18473	8
1 1/2	1	0.403	1	15588	8
1 1/2	1 1/4	0.410	1	78162	8
2	3/4	0.553	1	18468	8
2	1	0.583	1	15608	8
2	1 1/4	0.553	1	22328	8
2	1 1/2	0.635	1	78167	8


Viega ProPress reducer
Smart Connect technology

- For use with ASTM B88 and B75 tubing
- Copper
- Press connection

Components

EPDM sealing elements

Note

Must be installed with Viega ProPress XL-C rings and V2 actuator.

Model 0915.2XL

P1	P2	Wt [lb]	Quantity	Part No	DG
2 1/2	1	0.827	1	20685	8
2 1/2	1 1/4	0.851	1	20690	8
2 1/2	1 1/2	0.985	1	20695	8
2 1/2	2	1.047	1	20700	8
3	1 1/2	1.245	1	20705	8
3	2	1.289	1	20710	8
3	2 1/2	1.510	1	20715	8
4	2	2.089	1	20720	8
4	2 1/2	2.332	1	20725	8
4	3	2.482	1	20730	8


Viega ProPress reducer
Smart Connect technology

- For use with ASTM B88 and B75 tubing
- Copper
- Street, press connection

Components

EPDM sealing element

Model 2915.1

FTG (CTS)	P	Wt [lb]	Quantity	Part No	DG
3/4	1/2	0.097	10	78077	8
1	1/2	0.127	10	78082	8
1	3/4	0.144	10	78087	8
1 1/4	1/2	0.171	5	22333	8
1 1/4	3/4	0.195	5	78092	8
1 1/4	1	0.190	5	78097	8
1 1/2	3/4	0.277	1	14543	8
1 1/2	1	0.284	1	78102	8
1 1/2	1 1/4	0.304	1	78107	8
2	1	0.406	1	78112	8
2	1 1/4	0.418	1	78117	8
2	1 1/2	0.596	1	78122	8


Viega ProPress reducer
Smart Connect technology
Zero Lead

- For use with ASTM B88 and B75 tubing
- Bronze
- Street, press connection

Components

EPDM sealing element

Model 2915.1ZL

FTG (CTS)	P	Wt [lb]	Quantity	Part No	DG
1 1/2	1/2	0.325	5	79850	8
2	1/2	0.527	1	79855	8
2	3/4	0.521	1	79860	8

Couplings



Viega PureFlow Press coupling
Zero Lead
 - Bronze
 - Press connection
Model 2815ZL

P1	P2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.041	10	93000	6
1/2	3/8	0.048	10	93005	6
1/2	1/2	0.052	10	93020	6
3/4	1/2	0.070	10	93050	6
3/4	3/4	0.073	10	93040	6
1	3/4	0.113	10	93055	6
1	1	0.131	10	93060	6
1 1/4	3/4	0.187	5	93071	6
1 1/4	1	0.210	5	93065	6
1 1/4	1 1/4	0.260	5	93070	6
1 1/2	3/4	0.238	5	93072	6
1 1/2	1	0.246	5	93073	6
1 1/2	1 1/4	0.289	5	93075	6
1 1/2	1 1/2	0.317	5	93080	6
2	1 1/2	0.491	5	93091	6
2	2	0.573	5	93090	6



Viega PureFlow Press coupling
Smart Connect technology
 - Polymer
 - Press connection
Model V5615

P1	P2	Wt [lb]	Quantity	Part No	DG
3/8	3/8	0.022	25	49402	6
1/2	3/8	0.024	25	49342	6
1/2	1/2	0.027	25	49403	6
3/4	1/2	0.034	25	49343	6
3/4	3/4	0.040	25	49404	6
1	3/4	0.055	10	49354	6
1	1	0.068	10	49405	6
1 1/4	3/4	0.101	5	49347	6
1 1/4	1	0.112	5	49357	6
1 1/4	1 1/4	0.151	5	49407	6
1 1/2	3/4	0.118	5	49348	6
1 1/2	1	0.133	5	49358	6
1 1/2	1 1/4	0.165	5	49378	6
1 1/2	1 1/2	0.190	5	49408	6
2	1 1/2	0.270	1	49398	6
2	2	0.305	1	49409	6



Viega PureFlow Press test plug
Smart Connect technology
 - Polymer
 - Press connection
Model V5656

P	Wt [lb]	Quantity	Part No	DG
3/8	0.011	25	49722	6
1/2	0.015	25	49723	6
3/4	0.022	25	49744	6
1	0.038	10	49765	6
1 1/4	0.082	5	49770	6
1 1/2	0.095	5	49780	6
2	0.154	1	49790	6



Viega PureFlow Press transition coupling
Smart Connect technology
Zero Lead
 - For transitioning between Viega PureFlow
 Press and Viega ProPress
 - Bronze
 - Press connection
Components
 EPDM sealing elements
Note
 ProPress and PureFlow tool and jaws
 required
Model 2813PZL

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.076	10	99620	6
1/2	3/4	0.115	10	99626	6
3/4	1/2	0.078	10	99630	6
3/4	3/4	0.115	10	99640	6
1	3/4	0.136	10	99645	6
1	1	0.184	10	99660	6
1 1/4	1	0.236	5	99665	6
1 1/4	1 1/4	0.287	5	99670	6
1 1/2	1	0.276	5	99675	6
1 1/2	1 1/2	0.447	5	99680	6
2	1	0.459	5	99685	6
2	2	0.723	5	99690	6



Viega PureFlow Press adapter
Zero Lead
 - Bronze
 - Press connection, female pipe thread
Model 2812ZL

P	FPT	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.098	10	91520	6
1/2	3/4	0.135	10	91525	6
3/4	1/2	0.110	10	91541	6
3/4	3/4	0.141	10	91540	6
1	3/4	0.166	10	91545	6
1	1	0.239	10	91560	6
1 1/4	1 1/4	0.436	5	91570	6
1 1/2	1 1/2	0.511	5	91580	6
2	2	0.818	5	91590	6



Viega PureFlow Press adapter
Smart Connect technology
 - Bronze
 - Press connection
Components
 EPDM sealing elements
Model 2813PNG

P1	P2	Wt [lb]	Quantity	Part No	DG
5/8	1/2	0.081	5	69627	4
5/8	3/4	0.134	5	69628	4



Viega PureFlow Press transition coupling
Smart Connect technology
Zero Lead
 - For transitioning between Viega PureFlow Press and Viega ProPress
 - Bronze
 - Press connection
Components
 EPDM sealing elements
Note
 ProPress and PureFlow tool and jaws required
Model 2813PZL

P1	P2	Wt [lb]	Quantity	Part No	DG
1/2	1/2	0.076	10	99620	6
1/2	3/4	0.115	10	99626	6
3/4	1/2	0.078	10	99630	6
3/4	3/4	0.115	10	99640	6
1	3/4	0.136	10	99645	6
1	1	0.184	10	99660	6
1 1/4	1	0.236	5	99665	6
1 1/4	1 1/4	0.287	5	99670	6
1 1/2	1	0.276	5	99675	6
1 1/2	1 1/2	0.447	5	99680	6
2	1	0.459	5	99685	6
2	2	0.723	5	99690	6



Viega ProPress 90° extended street elbow
Smart Connect technology
 - For use with ASTM B88 and B75 tubing
 - Copper
 - Press connection, street
Components
 EPDM sealing element
Model 2947

P	FTG (CTS)	Wt [lb]	Quantity	Part No	DG
3/4	3/4	0.386	5	77353*	8

* = Available while supplies last



Viega ProPress insert stiffener
 - For Viega ProPress 90° extended street elbow
 - Suitable for Viega ProPress 90° extended street elbow Model 2947
 - Bronze
Model 2946

d	Wt [lb]	Quantity	Part No	DG
3/4	0.046	5	16423	4



Viega PureFlow Press adapter
 - Bronze
 - Press connection, female copper tube size
Model 2813.5NG

P	C	Wt [lb]	Quantity	Part No	DG
5/8	1/2	0.072	5	82027	4
5/8	3/4	0.108	5	82031	4