



U5240-O-200S

COLLAPSE PRODUCT IMAGE



Appears In:

[Western Region Catalog](#)

4 Terminal Ring Type Plain Top 1-200 Ampere Main Breaker Single Pedestal Direct Bury Series Wired 40 Block

SPECIFICATIONS

Brand Name	Milbank
Type	Ring Type Meter Socket
Special Features	Series Wired
Application	Mobile Home Power
Standard	UL Listed;Type 3R
Voltage Rating	Up to 240 Volts Alternating Current
Amperage Rating	200 Continuous Ampere
Phase	1 Phase
Frequency Rating	60 Hertz
Size	10.25L x 9.688W x 80H
Number of Main Breakers	1
Main Breaker Size	One 200 Ampere Main Breaker
Cable Entry	Underground
Terminal	Double Mechanical
Insulation	Glass Polyester
Mounting	Pedestal
Material	G90 Galvanized Steel with Powder Coat Finish
Number of Jaws	4 Terminal
Bypass Provision	No Bypass
Number of Meter Positions	Single Power Head
Equipment Ground	Ground Bar

SPECIFICATIONS

Hub/Closing Plate	Plain Top
Line Side Wire Range	6 AWG - 350 kcmil
Load Side Wire Range	1/0 AWG - 300 kcmil
Number Branch Circuits	4
Number Of Receptacles	0
Height	80 IN
Length	10.25 IN
Width	9.688 IN

Please consult serving utility for their requirements prior to ordering or installing, as specifications and approvals vary by utility and may require local electrical inspector approval. All installations must be installed by a licensed electrician and must comply with all national and local codes, laws and regulations. Milbank reserves the right to make changes in specifications and features shown without notice or obligation.