



Search Panduit.com



Search within category

BUY NOW

DESIGN / INSTALL



PLT3I-M

Pan-Ty® locking tie, intermediate cross section, 11.4" (290mm) length, nylon 6.6, natural, bulk package.

Specs	Packaging Details	Tools	Documents	★ Add to Favorites	🛒 Add to BOM
Product Type	Cable Ties				
Material	Nylon 6.6				
Application	General				
Color	Natural				
Cross Section	Intermediate				
Locking Style	Locking				
Min. Loop Tensile Strength Lbs. (N)	40 (178)				
Plenum-Rated	Yes, AH-2				
Tool	GTS, GTSL, GS2B, PTS, PPTS, STS2				
Length In (mm)	11.4 (290)				
Thickness In (mm)	0.052 (1.3)				
Bundle Diameter Range In. (mm)	0.06 (1.5) - 3.00 (76)				
CE Compliant	Yes				
CSA Certified	Yes				
Mil. Std. Part Number	—				
UL 62275 Compliant (Type 1, 11)	—				
UL 62275 Compliant (Type 2, 21)	Yes				
UL Listed (File #E56854)	Yes				
UL Recognized (File #E56854)	Yes				
Continuous Use Temperature Range	-76°F (-60°C) - 185°F (85°C)				
Environment	Plenum				
Installation Temperature	-4°F (-20°C) - 32°F (0°C)				
Material Flammability Rating	UL 94V-2				
Min. Loop Tensile Strength (N)	178				
Operating Temperature	-76°F (-60°C) - 185°F (85°C)				
Part Features	One-piece locking wedge for consistent performance and reliability. Low thread force and high loop tensile strength.				

Width In (mm)	0.145 (3.7)
RoHS Compliancy Status	Compliant
Min. Order Qty.	1,000.0000
