



Eaton Bussmann series high speed cylindrical fuse

FWH-5A14F

UPC:051712370790

Dimensions:

Height: 14 MMLength: 55 MMWidth: 14 MM

Weight:22.4 G

Warranties:

Not Applicable

Specifications:

• Type: Fuse

 Application: protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters

• Voltage Rating: 1200V

• Voltage Rating Numeric: 500 V

• Amperage Rating: 5A

• Amperage Rating Numeric: 5 A

• Interrupt Rating: 200 kAIC Vac, 50 kAIC at

500 Vdc

• Connection: Ferrule end X ferrule end

Construction Size: 14 x 51 mm
Packaging Type: Standard

• Breaking Capacity: 200 A

• Clearing (I2T): Clearing at 500V: 6.4

• Frequency Rating Maximum: 62 HZ

• Frequency Rating Minimum: 45 HZ

• Fuse Shape: cylindrical

• Fuse Indicator: Non Indicating

• Pre Arc (I2T): 1.6

• Release Characteristic: Other

• Utilization category: aR (accompanied

semiconductor protection)



Voltage Type: AC/DCWatt Losses: 1.5WWith Striker: No

Supporting documents:

Product Catalog

Certifications:

- CSA Certified
- UL Recognized

Product compliance:

CE Marked

© 2016 Eaton. All rights reserved.