

Eaton SC-25

Catalog Number: SC-25

Eaton Bussmann series SC fuse, Current-limiting time-delay fuse, Rejection style, 25 A, Class G, Non-indicating, Ferrule end x ferrule end, 12 sec at 200%, 10 kAIC at 300 Vdc|100 kAIC at 480 Vac, Standard, 480 V, 300 Vdc

General specifications

Product Name	Catalog Number
Eaton Bussmann series SC fuse	SC-25
UPC	Product Length/Depth
051712250252	1.62 in
Product Height	Product Width
0.41 in	0.41 in
Product Weight	Warranty
0.18 lb	Not Applicable
Compliances	
CE Marked	
RoHS Compliant	



Electrical rating

Amperage Rating

25 A

Interrupt rating

100 kAIC at 480 Vac

10 kAIC at 300 Vdc

Response time

12 sec at 200%

Voltage rating

480 Vac, 300 Vdc

Physical details

Packaging type

Standard

General information

Class

Class G

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Special features

Ferrule design, Type P

Resources

Catalogs

[Bussmann series complete full line catalog no. 1007](#)

Multimedia

[Bussmann series Fuseology](#)

Specifications and datasheets

[Eaton Specification Sheet - SC-25](#)

Technical data sheets

[Bussmann series SC Class G Fuse Data Sheet No. 1024](#)

[SC-25~BUSS SC FUSE CLASS G CLASS G](#)

Technical service bulletins

[Datasheet - FNQ-30](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)