



Powering Business Worldwide

[pe.eaton.com](http://pe.eaton.com)

## Definite Purpose Control - Contactor

**C25FNF260T**

**UPC:**782113476124

### Dimensions:

- **Height:** 3.75 IN
- **Length:** 3.97 IN
- **Width:** 2.63 IN

**Weight:**2.8 LB

**Notes:**Resitive Load rating per pole

### Warranties:

- 1 year

### Specifications:

- **Amperage Rating:** 60A
- **Coil:** 24 Vac, 50/60 Hz
- **Enclosure:** Open with metal mounting plate
- **Frame Size:** 60-75A, two- and three-pole
- **Model:** Contactor
- **Number Of Poles:** Two-pole
- **Resistive Load:** 75A
- **Terminals:** Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)
- **Type:** Non-reversing

### Supporting documents:

- [Eatons Volume 5-Motor Control and Protection](#)
- [C25FNF2 AutoCAD 2D Footprint \(mm\)](#)
- [C25FNF2 3D Inventor](#)
- [C25FNF2 2D PDF](#)
- [C25FNF2 AutoCAD 2D Footprint](#)
- [C25FNF2 2D Drawing Xchange](#)
- [C25FNF2 3D Model Xchange](#)
- [Eaton Specification Sheet - C25FNF260T](#)

### Certifications:



- CSA Certified
- UL Recognized

**Product compliance:** No Data

---

© 2016 Eaton. All rights reserved.