



Surge Protection: Whole House Surge Protection

Smart Guard® Whole House Surge Protective Device with IModule™ | IG2240-PK

Smart Guard® Whole House Surge Protective Device with IModule™
IG2240-PK



Features & Applications

Features

- Six Modes of protection
- TPMOV® surge protection technology
- Includes three IModules with LED power and protection status lights
- IModules replace quickly and easily, eliminating the need to install a new SPD unit
- Tamper-proof IModule doors, will only open when IModule is being inserted
- Type 3R Rainproof Enclosure for indoor/outdoor applications in plastic
- 10-year product warranty
- \$25,000 connected equipment warranty for 10 years on appliances and electronics
- UL certified to ANSI/UL 1449 3rd edition

Applications

- Residential
- Light Commercial

Specifications

Modes of Protection 6 (L1-N, L2-N, L1-G, L2-G, N-G, L1-L2)	Maximum Continuous Operating Voltage (L-L) 300	Operating Temperature Max (F) 185
Surge Protection Type 2	Maximum Continuous Operating Voltage (L-N) 150	Operating Temperature Min (°C) -35
Nominal Discharge Current 10 kA	Maximum Continuous Operating Voltage (N-G) 150	Operating Temperature Min (F) -31
Short Circuit Current Rating 10 kA	Voltage Protection Rating (L-G) 1500	Number of Wire Leads 4
Surge Protection TPMOV®	Voltage Protection Rating (L-L) 1200	Wire Lead Length (in) 18
Wiring Option Terminals, Wire Leads	Voltage Protection Rating (L-N) 800	Wire Lead Length (mm) 457.2
Enclosure Type Indoor/Outdoor Type 3R Plastic	Voltage Protection Rating (N-G) 700	Warranty 10-year
Maximum Continuous Operating Voltage (L-G) 300	Operating Temperature Max (°C) 85	Connect Equipment Warranty Period 10-year

Related Accessories and Parts (1)





IModule™ Replacement Module for
Smart Guard

IG120RSM10K

Copyright © 2017 Intermatic Incorporated. All rights reserved.