

PRODUCT-DETAILS

CPL3/4SA-G

PVC CTD COND CPLG 3/4IN ALUM GRAY



General Information

Extended Product Type	CPL3/4SA-G
Product ID	7TAA087750R0033
EAN	5415022340365
Catalog Description	PVC CTD COND CPLG 3/4IN ALUM GRAY
Long Description	PVC Coated Conduit Coupling, 3/4 Inch/21 Metric Coupling Size, 1.53 Inch/38.91 Millimeters Minimum Length of Metal, 3.75 Inch/95.25 Millimeters Total Minimum Length Including Sleeve, Straight Threads, Pressure Sealing Sleeves, Blue Urethane Coating on Interior and Threads, Aluminum, Gray

Ordering

EAN	5415022340365
-----	---------------

Dimensions

Product Net Depth / Length	3.75 in 95.25 mm
Product Net Weight	.15 lb 68.027 g

Container Information

Package Level 2 Units	90 piece
Package Level 2 Width	13.75 in

	349 mm
Package Level 2 Height	7.75 in
	197 mm
Package Level 2 Depth / Length	16.5 in
	419 mm

Additional Information

Application	Corrosion-Protected Connections for Conduit Sections
Brand / Label	Ocal
Color	Gray
Material	Aluminum
Nominal Size	3/4 in
	21 mm
Number of Batteries	0
Product Name	INSULATED FITTING FOR CONDUIT
Product Type	Conduit Coupling
Special Functions	Pressure-Sealing Sleeves Protect Your Connection
UPC	704508362591

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	CPL3/4SA-G
Instructions and Manuals	CPL3/4SA-G

Classifications

ETIM 6	EC000939 - Coupler for installation tubes
ETIM 7	EC000939 - Coupler for installation tubes
UNSPSC	39131707
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5548 >> Electrical conduit coupling

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Rigid Cable Protection Systems

