

Halogen Lamps

EcoVantage Lamps

Watts	Bulb	Base	Product Number	Symbols, Footnotes	Ordering Code	Volts	Pkg. Qty.†	Description	Class Filament	MOL (In.)	Rated Avg. Life (Hrs.)(93)	Approx. MBCP	Lumens	Life Years (446)	Energy Cost (445)	Color Temp. (K)
EcoVantage Decorative Boxed (97)													FTC REQUIREMENTS*			
40	G25	Med.	42084-4	†	40G25/EV/CL	120	12	Clear	C, CC-8	4%	2200	—	550	2.0	\$4.82	2800
			42085-1	†	40G25/EV/W	120	12	White	C, CC-8	4%	2200	—	500	2.0	\$4.82	2800

EcoVantage Halogen Pro PAR20 Lamps (82, 86)

39	PAR20	Med.	42512-4	†	39PAR20/EVP/SP10	120	15	Spot 10°	C, CC-8	3%	1100	3840	500	1.0	\$4.70	2900
			42520-7	†	39PAR20/EVP/FL25	120	15	Flood 25°	C, CC-8	3%	1100	865	500	1.0	\$4.70	2900

EcoVantage Halogen Pro PAR30S Lamps (82, 86)

39	PAR30S Med.	42891-2	†	39PAR30S/EVP/SP10	120	15	Spot 10°	C, CC-8	3%	1100	6300	530	1.0	\$4.70	2900
		42896-0	†	39PAR30S/EVP/FL25	120	15	Flood 25°	C, CC-8	3%	1100	1870	530	1.0	\$4.70	2900
53	PAR30S Med.	42888-8	⊕† (104)	53PAR30S/EVP/SP10	120	15	Spot 10°	C, CC-8	3%	1100	10,000	920	1.0	\$6.38	2860
		42890-4	⊕† (104)	53PAR30S/EVP/FL25	120	15	Flood 25°	C, CC-8	3%	1100	3100	920	1.0	\$6.38	2860
		42898-6	⊕† (104)	53PAR30S/EVP/WFL40	120	15	Wide Flood 40°	C, CC-8	3%	1100	1400	920	1.0	\$6.38	2860

EcoVantage Halogen Pro PAR30L Lamps (82, 86)

39	PAR30L Med.	42887-0	†	39PAR30L/EVP/FL25	120	15	Flood 25°	C, CC-8	4%	1100	1870	520	1.0	\$4.70	2900
53	PAR30L Med.	42892-0	⊕† (104)	53PAR30L/EVP/FL25	120	15	Flood 25°	C, CC-8	4%	1100	3100	920	1.0	\$6.38	2860
		42895-2	⊕† (104)	53PAR30L/EVP/WFL40	120	15	Wide Flood 40°	C, CC-8	4%	1100	1400	920	1.0	\$6.38	2860

EcoVantage Halogen Pro PAR38 Lamps (82, 86)

39	PAR38 Med.Skt.	42886-2	†	39PAR38/EVP/SP10	120	12	Spot 10°	C, CC-8	5%	1100	7000	570	1.0	\$4.70	2900
		42884-7	†	39PAR38/EVP/FL25	120	12	Flood 25°	C, CC-8	5%	1100	1900	570	1.0	\$4.70	2900
53	PAR38 Med.Skt.	42889-6	⊕† (104)	53PAR38/EVP/SP10	120	12	Spot 10°	C, CC-8	5%	1100	11,000	920	1.0	\$6.38	2860
		42885-4	⊕† (104)	53PAR38/EVP/FL25	120	12	Flood 25°	C, CC-8	5%	1100	3250	920	1.0	\$6.38	2860
72	PAR38 Med.Skt.	42894-6	⊕† (104)	72PAR38/EVP/SP10	120	12	Spot 10°	C, CC-8	5%	1100	16,000	1350	1.0	\$8.67	2880
		42893-8	⊕† (104)	72PAR38/EVP/FL25	120	12	Flood 25°	C, CC-8	5%	1100	4500	1350	1.0	\$8.67	2880

For the most current product information, go to the e-catalog on www.philips.com
Halogen symbols and footnotes located on page 109

