



Ceramalux Non-ALTO

C50S68/M 12pk

Philips Ceramalux lamps provide efficient lighting solutions for industrial applications, warehouses, post top applications and parking lots.

Product data

| General Information | |
|------------------------------------|------------------------------------|
| Base | E26 [Single Contact Medium Screw] |
| Operating Position | Universal [Universal] |
| Main Application | General Lighting (G) |
| ANSI Code HID | S68 |
| Light Technical | |
| Luminous Flux (Rated) (Min) | 3550 lm |
| Luminous Flux (Rated) (Nom) | 4000 lm |
| Design Mean Lumens | 3600 lm |
| Chromaticity Coordinate X (Nom) | 540 |
| Chromaticity Coordinate Y (Nom) | 415 |
| Correlated Color Temperature (Nom) | 2100 K |
| Luminous Efficacy (Rated) (Min) | 71 lm/W |
| Luminous Efficacy (rated) (Nom) | 80 lm/W |
| Color Rendering Index (Nom) | 12 |
| Operating and Electrical | |
| Lamp Current (Nom) | 1.18 A |
| Ignition Supply Voltage (Max) | 110 V |
| Re-Ignition Time (Min) (Max) | 2 min |
| Ignition Time (Max) | 5 s |
| Voltage (Max) | 62 V |
| Voltage (Min) | 46 V |


| Voltage (Nom) | 52 V |
|---------------------------------|--------------------|
| Mechanical and Housing | |
| Bulb Finish | Clear |
| Cap-Base Information | Brass [Brass Cap] |
| Bulb Material | Hard Glass |
| Approval and Application | |
| Mercury (Hg) Content (Max) | 17.7 mg |
| Luminaire Design Requirements | |
| Bulb Temperature (Max) | 400 °C |
| Cap-Base Temperature (Max) | 190 °C |
| Product Data | |
| Order product name | C50S68/M 12pk |
| EAN/UPC - Product | 046677467302 |
| Order code | 467308 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 12 |
| Material Nr. (12NC) | 928601144990 |
| Net Weight (Piece) | 55.000 g |

Warnings and Safety

Ceramalux Non-ALTO

Dimensional drawing

| Product | D | C (max) |
|---------------|----------|----------|
| C50S68/M 12pk | 2.125 in | 5.438 in |



HPS R 50W E26 BD17 U

