



T8

8.5T8/MAS/36-850/IF14/P 10/1

Our TLEDs are available in InstantFit (Type A / Type C) or MainsFit (Ballast bypass / Type B) versions. The InstantFit lamps work on a broad variety of ballasts and LED drivers. Only InstantFit has over 15,000 lamp & ballast combinations delivering even light output, energy savings and a long lifetime. Our MainsFit products feature a double-ended design, simplifying installation while a proprietary safety circuit minimizes a shock risk. Lamp sizes range from 2-foot to 8-foot and U-bend with a variety of lumen outputs.


Product data

General Information	
Base	G13 [Medium Bi-Pin Fluorescent]
EU RoHS compliant	Yes
Nominal Lifetime (Nom)	70000 h
Switching Cycle	50000X
Light Technical	
Color Code	850 [CCT of 5000K]
Beam Angle (Nom)	180 °
Initial lumen (Nom)	1400 lm
Correlated Color Temperature (Nom)	5000 K
Color Consistency	<5
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	20K to 120K Hz
Power (Rated) (Nom)	8.5 W
Starting Time (Nom)	0.5 s
Warm Up Time to 60% Light (Nom)	0.5 s
Power Factor (Nom)	
Power Factor (Nom)	0.9
Voltage (Nom)	
Voltage (Nom)	120-277, 347 V
Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	50 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Product Length	900 mm
Approval and Application	
Energy Saving Product	Yes
Approbation Marks	RoHS compliance UL certificate DLC compliance

Energy Certifications	DLC Standard
DesignLights Consortium Qualified Product List -	
Product Data	
XUCDM.COPY.Product.Title	8.5T8/MAS/36-850/IF14/P 10/1
EAN/UPC - Product	046677539887
Order code	539882

Numerator – Quantity Per Pack	1
Numerator – Packs per outer box	10
Material Nr. (12NC)	929001967704
Net Weight (Piece)	0.160 kg
Model Number	9290019677


Dimensional drawing




TLED IF MasterClass 3ft 1400lm 5000K

Product	D1	D2	A1	A2	A3
8.5T8/MAS/36-850/ IF14/P 10/1	25.7 mm	26.3 mm	893.4 mm	900.5 mm	907.6 mm


Photometric data



G13 5000K 1400lm





G13 4000K




G13 5000K 1400lm


Lifetime




G13 4000K



G13 4000K



G13 4000K



G13 4000K

G13 4000K

