



Thin-Wall Heat-Shrinkable Tubing

T&B Catalog Number:

HS-KIT

UPC Number:

78621093898

Status:

Active

Description:

Thin-Wall Heat Shrinkable Tubing Assortment precut in 6 inch lengths, black - (32)-DIA. 3/16", (20)-DIA. 1/4", (8)-DIA. 3/8", (6)-DIA. 1/2", (4)-DIA. 3/4", (4)-DIA. 1", includes plastic storage case

Features

Flame-retardant, cross-linked polyolefin.

Meets UL 224, 125°C; CSA 22.2 No. 198.1, 125°C;

MIL-DTL-23053/5 Class 1&2; AMS 3636 & 3637;

DEF STAN 59-97, Issue 3, Type 2a

General

Style CPO Series Non-Lined - Kit

Color Black

Temperature Range -55°C - 135°C

Shrink Ratio 2:1

Specifications

Shrink Temperature 120°C

Packaging

T&B Order Multiple 1

Package in Units 1

T&B Sold in UOM Each

T&B Weight Per UOM 140 lbs. per 100

Application Support

Specifications Available on Website

Overview Available on Website

Notes

UL Recognized File Number E137759 and CSA Certified. Clear material not UL Recognized.

Certifications

RoHS Compliance Yes

Certifications



For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com