PRO SERIES SERVICE FITTINGS

Compatible with Walkerduct Pro Series only


Walkerduct Pro Series Flush Brushed Aluminum Flanges Ordering Information

828DLRAL Brushed Aluminum Single Locking Receptacle Cover Plate



Single flip lid cover for 20A or 30A single locking receptacles. Device opening is 2 5/8" (67mm). For use with maximum female locking device of 1.58" diameter, and maximum male plug face of 2.25" diameter.

828GFITCAL Brushed Aluminum GFI Cover Plate




May be used with Activate and Ortronics* Connectivity Systems in conjunction with 817, 827, and 837 Series flanges.

NOTE: Brass covers and flanges are not interchangeable with aluminum or nonmetallic covers and flanges.

Nonmetallic covers are interchangeable with aluminum flanges.


818TCAL One-Gang Brushed Aluminum Combination Carpet & Tile Flange



Accepts Ortronics* MAB6TJ TracJack and MAB3S2 Series II bezels, Activate CM-MAB bezel, and Wiremold Open System inserts, all sold separately.


NOTE: Brushed aluminum flange comes with a beveled edge.

828DPGFITCAL Brushed Aluminum Rectangular Cover Plate



Allows for mounting of a duplex style receptacle with a rectangular flip lid cover plate.


828TCAL Two-Gang Brushed Aluminum Combination Carpet & Tile Flange



Accepts Ortronics® MAB6TJ TracJack and MAB3S2 Series II adapters and Wiremold CM Series inserts, sold separately.

NOTE: Brushed aluminum flange comes with a beveled edge.


830CKTCAL Brushed Aluminum Cover Plate



Power or communication plate with 2" (51mm) and 1 1/4" (32mm) plugs.

NOTE: Acceptable for use with threaded conduit when passing through power cables.


838TCAL Three-Gang Brushed Aluminum Combination Carpet & Tile Flange



Accepts Ortronics* MAB6TJ TracJack and MAB3S2 Series II bezels, Activate CM-MAB bezel, and Wiremold Open Systems inserts, all sold separately.

NOTE: Brushed aluminum flange comes with a beveled edge.


830CKTCAL-1 Brushed Aluminum Cover Plate



Power or communication plate with 2" (51mm) and 1" (25mm) plugs.


NOTE: Acceptable for use with threaded conduit when passing through power cables.

828R-TCAL Brushed Aluminum Duplex Cover Plate




Flip lids. Can also be used with a 106 type communication bezel.

830CKTCAL-3/4 Brushed Aluminum Cover Plate



Power or communication plate with 2" (51mm) and 3/4" (19.1mm) plugs.

830CKTCAL-1/2 Brushed Aluminum Cover Plate



Power or communication plate with 2" (51mm) and 1/2" (12.7mm) plugs.