


WORKSTATION SURGE SOLUTIONS

Ordering Information


Work Station Power Solutions – Surge Protected Plug-In Outlet Center Units Ordering Information

M5S Plug-In Outlet Center Units




Sentrex® high performance surge protection. Five outlets, lighted switch, durable putty white aluminum housing, 15A. Receptacles rotated 90° and spaced to accommodate transformers. Length 24" (610mm). 6' (1.8m) 14/3 SJT putty white cord with NEMA5-15 plug. Snap-on, slide-off mounting.

7700N Basic Surge Protection



8 outlets spaced for plug-in transformers, lighted switch, impact-resistant putty white polymeric housing. 15A. 6' (1.8m) 14/3 SJT putty white cord with NEMA 5-15 plug. Maximum surge current 6500 Amps. 14" x 4 1/4" x 1 1/2" (356mm x 108mm x 38mm). Keyhole mounting.

Plug-In Outlet Center Units



PART NUMBERS:


M6S (6 Foot Cord)

M6S-15 (15 Foot Cord)

Sentrex® high performance surge protection. Six outlets, lighted switch, durable putty white aluminum housing, 15A. 6' (1.8m) (M6S) or 15' (4.6m) (M6S-15) 14/3 SJT putty white cord with NEMA5-15 plug. Length 15 1/4" (387mm). Snap-on, slide-off mounting.


77001N

Basic Surge Protection Plus Phone/Fax Protection




8 outlets spaced for plug-in transformers, lighted switch, impact-resistant putty white polymeric housing. 15A. 6' (1.8m) 14/3 SJT putty white cord with NEMA 5-15 plug. Maximum surge current 6500 Amps. 14" x 4 1/4" x 1 1/2" (356mm x 108mm x 38mm). Keyhole mounting.

M5BZ Plug-In Outlet Center Units




Perma-Power® computer grade surge protection. Five outlets, lighted switch, durable putty white aluminum housing, 15A. Receptacles rotated 90° and spaced to accommodate transformers. 6' (1.8m) 14/3 SJT putty white cord with NEMA5-15 plug. Length 21" (533mm). Snap-on, slide-off mounting.

77002N Basic Surge Protection Plus Digital Satellite, Coax and Phone/Fax Protection



8 outlets spaced for plug-in transformers, lighted switch, impact-resistant putty white polymeric housing. 15A. 6' (1.8m) 14/3 SJT putty white cord with NEMA 5-15 plug. Maximum surge current 6500 Amps. 14" x 4 1/4" x 1 1/2" (356mm x 108mm x 38mm). Keyhole mounting.

Plug-In Outlet Center Units




PART NUMBERS:

M6BZ (6 Foot Cord)

M6BZ-15 (15 Foot Cord)

Perma-Power® computer grade surge protection. Six outlets, lighted switch, durable putty white aluminum housing, 15A. 6' (1.8m) (M6BZ) or 15' (4.6m) (M6BZ-15) 14/3 SJT putty white cord with NEMA5-15 plug. Length 13 1/4" (337mm). Snap-on, slide-off mounting.

Plug-In Outlet Center Units



Right Angle Plug

PART NUMBERS:

M6BZNET (6 Foot Cord)

M6BZNET-15 (15 Foot Cord)

Six outlets, two spaced for transformers. Lighted switch, data line protector with RJ45 jacks. 6' (1.8m) (M6BZNET) or 15' (4.6m) (M6BZNET-15) power cord with 45° right angle plug. Length 18" (457mm).