


# 2400D SERIES™ RACEWAY

## 2400D Series Raceway Fittings Ordering Information (continued)


### Cover Clip


**PART NUMBERS:**

**V2406** (Ivory)  
**2406-FW** (Fog White)

Covers seam where two lengths of 2400D Series Raceway come together (nonmetallic).


### Divided Blank End Fitting


**PART NUMBERS:**

**V2410BD** (Ivory)  
**2410BD-FW** (Fog White)

Closes off open end of 2400D Series Raceway.


### Divided Entrance End Fitting


**PART NUMBERS:**

**V2410D** (Ivory)  
**2410D-FW** (Fog White)

Feeds 2400D Series Raceway. Back has two 1/2" trade size KOs and two rectangular KOs for communication cabling. Additional 1" and 3/4" concentric trade size KO on each side.


### Divided Entrance End Fitting


**PART NUMBERS:**

**V2410DFO** (Ivory)  
**2410DFO-FW** (Fog White)

Feeds 2400 & 2400D Series Raceway. Includes 1/2", 3/4", and 1" trade size KOs on back and end. Removable/adjustable divider and radiused insert included


### Divided Flat Elbow


**PART NUMBERS:**

**V2411D** (Ivory)  
**2411D-FW** (Fog White)

Right angle turns on the same surface.


### Radiused Divided Flat Elbow


**PART NUMBERS:**

**V2411DFO** (Ivory)  
**2411DFO-FW** (Fog White)

90° flat elbow with integral dividers. Provides 2" (51mm) full capacity cable bend radius control for fiber optic and UTP/STP cable installations. Ideal for lay-in or pull-through installations. Two couplings included.


### Radiused Divided Tee


**PART NUMBERS:**

**V2415DFO** (Ivory)  
**2415DFO-FW** (Fog White)

For branching raceway at right angles. Provides 2" (51mm) cable bend radius control for fiber optic and UTP/STP cable installations. Couplings included.


### Divided Internal Elbow


**PART NUMBERS:**

**V2417D** (Ivory)  
**2417D-FW** (Fog White)

Internal 90° corners.


### Radiused Divided Internal Elbow


**PART NUMBERS:**

**V2417DFO** (Ivory)  
**2417DFO-FW** (Fog White)

90° internal corner provides 2" (51mm) cable bend radius control for fiber optic and UTP/STP cable installations. Two couplings included.

### Radiused Divided External Elbow


**PART NUMBERS:**

**V2418DFO** (Ivory)  
**2418DFO-FW** (Fog White)

90° external elbow provides 2" (51mm) cable bend radius control for fiber optic and UTP/STP cable installations. Two couplings included.