

Submitted Model No.: \_\_\_\_\_  
 Specific Features: \_\_\_\_\_



see what Delta can do™

# PERSONAL HAND HELD SHOWERS

## ■ Touch-Clean® Nozzles

### STANDARD SPECIFICATIONS:

- Maximum 2.5 gpm @ 80 psi, 9.5 L/min @ 550 kPa (57014 only)
- Maximum 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa
- Hand held shower with one or three spray settings
- 60"-82" stretchable metal hose
- Certified dual check valves for backflow protection
- 24" (610 mm) wall bar with adjustable slide (allows for adjustable shower height) - 57014, 57021, 57051 and 57085 only. Not to be used as a Grab Bar. Not ADA compliant
- Wall mount bracket - 55013, 55020, 55021, 55051 and 55085 only

### WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes: or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

### COMPLIES WITH:

- ASME A112.18.1/CSA B125.1 ♦
- EPA WaterSense®

|                                                                                                                                                                                                                 |                                                                                                                                                                                           |                                                                                                                                                                   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><b>57014▲ 2.5 GPM</b></p> <p>24" (610mm)</p> <p>60"-82" (1524 mm-2083 mm)</p> <p>Full Body Spray</p> <p>Massage Spray</p> <p>Soft Drench Spray</p> <p>Accepts 1/2" - 14 NPSM Male</p>                        | <p><b>57021▲ 1.75 GPM</b></p> <p>24" (610mm)</p> <p>60"-82" (1524 mm-2083 mm)</p> <p>Full Body Spray</p> <p>Massage Spray</p> <p>Soft Drench Spray</p> <p>Accepts 1/2" - 14 NPSM Male</p> | <p><b>57051▲ 1.75 GPM</b></p> <p>25 3/4" (654 mm)</p> <p>60"-82" (1524 mm-2083 mm)</p> <p>Full Body Spray</p> <p>Accepts 1/2" - 14 NPSM Male</p>                  |
| <p><b>57085▲ 1.75 GPM</b></p> <p>24" (610mm)</p> <p>60"-82" (1524 mm-2083 mm)</p> <p>Full Body Spray</p> <p>Accepts 1/2" - 14 NPSM Male</p>                                                                     | <p><b>55013▲ 1.75 GPM</b></p> <p>2 1/4" (57 mm)</p> <p>4" (102 mm)</p> <p>Full Body Spray</p> <p>60"-82" (1524 mm-2083 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>                         | <p><b>55020▲ 1.75 GPM</b></p> <p>2 1/4" (57 mm)</p> <p>4" (102 mm)</p> <p>Full Body Spray</p> <p>60"-82" (1524 mm-2083 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p> |
| <p><b>55021▲ 1.75 GPM</b></p> <p>2 1/4" (57 mm)</p> <p>4" (102 mm)</p> <p>Full Body Spray</p> <p>Massage Spray</p> <p>Soft Drench Spray</p> <p>60"-82" (1524 mm-2083 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p> | <p><b>55051▲ 1.75 GPM</b></p> <p>2 3/8" (61 mm)</p> <p>4 1/16" (104 mm)</p> <p>Full Body Spray</p> <p>60"-82" (1524 mm-2083 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p>                    | <p><b>55085▲ 1.75 GPM</b></p> <p>2 1/4" (57 mm)</p> <p>4" (102 mm)</p> <p>Full Body Spray</p> <p>60"-82" (1524 mm-2083 mm)</p> <p>Accepts 1/2" - 14 NPSM Male</p> |

### ▲ Designate proper finish suffix

- ◆ Your Delta Faucet handshower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or [www.deltafaucet.com](http://www.deltafaucet.com) for finish options and product availability.

DSP-B-55021 Rev. C

**Delta Faucet Company**  
 55 E. 111th Street, Indianapolis, IN 46280  
 350 South Edgeware Road, St. Thomas, ON N5P 4L1  
 © 2017 Delta Faucet Company