

QUICKTRONIC® High Efficiency T8 Instant Start Systems



32 T8 Instant Start Universal Voltage (120-277V) Lamp Striation Control

Item Number	OSRAM SYLVANIA Description	Input Current (AMPS)	Lamp Type	Rated Lumens (lm)	No. of Lamps	Ballast Factor (BF)	Initial System Lumens	Mean System Lumens	Input Power (W)	System Efficacy ² (lm/W)	BEF ¹
LOW BALLAST FACTOR											
49837 49861	QHE 1X32T8/UNV ISL-SC Banded Pack 10-Pack	0.21/0.09	F032/700	2600	1	0.78	2030	1865	25	81	3.12
		0.21/0.09	F032/XP/XL	2950	1	0.78	2300	2210	25	92	3.12
		0.19/0.08	F028/XP/XL/SS	2600	1	0.78	2030	1865	22	92	3.55
		0.21/0.09	F032/XP	3000	1	0.78	2340	2200	25	94	3.12
		0.20/0.09	F030/XP/SS	2850	1	0.78	2225	2090	24	93	3.25
		0.19/0.08	F028/XP/SS	2725	1	0.78	2125	2000	22	97	3.55
		0.17/0.08	F025/XP/SS	2500	1	0.78	1930	1815	20	97	3.90
		0.13/0.06	LED19T8/L48/8XX/SUB	—	1	—	—	1600	15	107	—
49838 49863	QHE 2X32T8/UNV ISL-SC Banded Pack 10-Pack	0.41/0.18	F032/700	2600	2	0.78	4055	3730	48	84	1.63
		0.21/0.09	F032/XP/XL	2950	2	0.78	4600	4410	48	96	3.12
		0.35/0.15	F028/XP/XL/SS	2600	2	0.78	4060	3894	42	97	1.86
		0.41/0.18	F032/XP	3000	2	0.78	4680	4400	48	98	1