



# PRODUCT DATA SHEET

94 Eagle Fork Rd Hayesville, NC 28904  
 Ph: 800.343.2579 Fax: 828.389.3922

**Part Number:** 912202SD  
**Description:** 22 AWG two-conductor Shielded and Drain with a plenum rated PVC jacket.  
**Suitable Application:** Sound, Audio, Security, and Data Communication

**Construction Details:**

Total Number Conductors	2
Conductor Material	22 AWG 7-strand bare copper
Insulation Material	Low smoke copolymer
Insulation/Dielectric Thickness	.007"
Nominal Insulation Diameter	.043"
Color Code	Black/Red
Cabling Overall Lay	2.5" left hand lay
Tape Material	Aluminum / Mylar Foil
Drain Wire Material	24 AWG 7 strand tinned copper
Final Jacket Material	Low smoke copolymer
Nominal Thickness	.015"
Jacket Color	White (Other colors available upon request)
Nominal Jacket Diameter	.120"
Ripcord	Yes

**Print (Surface Print)**

Inkjet	Yes
Sequential Foot Marks	Yes

**Print Generic Sample Legend:**

**22 AWG 2C SHIELDED (UL) TYPE CL3P/FPLP OR c(UL)us TYPE CMP E179335**

**Electricals:**

Voltage Rating	300 volts
Capacitance CDR	59 pf/ft
Conductors	ASTM B-8
Temperature Rating:	-4C to +75°C
Impedance	37 Ω

**Applicable Standards:**

UL Type	CMP, CL3P, FPLP
ROHS Compliant	Yes

Customer Name: \_\_\_\_\_ Date Signed: \_\_\_\_\_

Customer Approval: \_\_\_\_\_

Specification Issue Date: 5/24/12

Rev. 06/09/2020