



## Product Data Sheet

94 Eagle Fork Rd Hayesville, NC 28904  
Ph: 800.343.2579 Fax: 828.389.3922

**Part Number:** 912206SD  
**Description:** 22 AWG 6 conductor with shield and drain, Plenum rated  
**Suitable Application:** Communication and Security

---

### Construction Details:

Total Number Conductors	6
Awg	22
Stranding	7 Strand
Conductor Material	Bare copper
Insulation Material	Low smoke copolymer
Insulation Thickness	.008"
Nominal Insulation Diameter	.043"
Color Code	Black, White, Red, Green, Brown, Blue
Cabling Overall Lay	3 " left hand lay
Tape Material	Aluminum Mylar
Final Jacket Material	Low smoke copolymer
Drain Wire Material	24 AWG stranded tinned copper
Nominal Thickness	.015"
Jacket Color	White
Nominal Jacket Diameter	.163"
Ripcord	Yes

---

### Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

### Print Generic Sample Legend:

**22 AWG 6C SHIELDED (UL) TYPE CL3P/FPLP OR c(UL)us TYPE CMP E179335**

---

### Applicable Standards:

Voltage Rating	300 volts	UL Type	CMP, CL3P, FPLP
Temperature Rating:	-4°C to +75°C	ROHS Compliant	Yes

Customer Name: \_\_\_\_\_ Date Signed: \_\_\_\_\_

Customer Approval: \_\_\_\_\_

Specification Issue Date: 4/5/12

Rev. 01/25/19