



Part Number: 912204SD
Description: 22 AWG 4-conductor shielded with Plenum rated insulation and jacket
Suitable Application: Communication and Security

Construction Details:

Total Number Conductors	4
Conductor Material	22 AWG 7-strand Bare Copper
Insulation Material	Low smoke polyvinyl chloride
Insulation Thickness	.007"
Nominal Diameter over Insulation	.043"
Conductor Color Code	Black, Red, Green, White
Tape Material	Aluminum / Mylar
Drain Wire Material	24 AWG 7-strand tinned copper
Cabling Overall Lay	2.5 " left hand lay
Final Jacket Material	Low smoke copolymer
Nominal Jacket Thickness	.015"
Jacket Color	White (Other colors available upon request)
Nominal Diameter over Final Jacket	.138"
Ripcord	Yes

Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

Print Generic Sample Legend:

22 AWG 4C SHIELDED (UL) TYPE CL3P/FPLP OR c(UL)us TYPE CMP E179335

Electricals:

Voltage Rating	300 Volts
Temperature Rating:	-4°C to +75°C

Applicable Standards:

UL Type	CMP, CL3P, FPLP
ROHS Compliant	Yes

Customer Approval Signature: _____ Date: _____

Customer Name: _____

Specification Issue Date: 4/20/10; Revised: 07/08/2020