



### Overview

Lead time	Usually in Stock
-----------	------------------



### General

Provided equipment	Installation guide
--------------------	--------------------

### Physical

Maximum Depth	5.67 in (14.4 cm)
Height	4.21 in (10.7 cm)
Net Weight	10.32 lb(US) (4.68 kg)
Width	4.21 in (10.7 cm)

### Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

### Batteries & Runtime

Battery Placement	Internal Battery
Battery blocks per string	2
Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
Battery voltage	24 V
Battery type	Lead-Acid battery
RBC Quantity	1

### Ordering and shipping details

Category	09305 - INDUSTRIAL UPS
GTIN	00731304291732
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	VN

## Packing Units

Package 1 Height	9.02 in (22.9 cm)
Package 1 width	9.02 in (22.9 cm)
Package 1 Length	9.02 in (22.9 cm)
Number of Units in Package 3	100

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------