

Uponor PEX-a Plumbing Systems

Uponor AquaPEX Tubing

Uponor AquaPEX tubing is used in hot and cold water distribution systems and AquaSAFE Residential Fire Safety Systems. Uponor AquaPEX tubing is suitable for use in hydronic heating and cooling applications where the system contains no ferrous corrodible components or where any ferrous components are isolated from the tubing. Uponor AquaPEX tubing coils and straight lengths come in red, white and blue for potable-water applications, and purple for water-reclamation applications.

Uponor AquaPEX tubing is manufactured and listed to ASTM F876 and F877 and CSA B137.5, certified to NSF Standards 14 and 61 and listed by the Hydrostatic Stress Board of PPI at 200°F at 80psi, 180°F at 100psi and 73.4°F at 160psi. Uponor AquaPEX tubing (½", ¾" and 1" only) is also listed to UL 1821 and ULC/ORD C199P and carries an additional rating of 120°F at 130psi.

Uponor AquaPEX White tubing is marked with the PEX 5106 designation as required by the most recent edition of ASTM F876-13, indicating it exceeds ASTM F876 chlorine-resistance requirements for continuous-recirculation systems operating up to 140°F while also affording a 1-month UV-resistance level.

Uponor AquaPEX Red and Blue tubing is marked with the PEX 5206 designation as required by the most recent edition of ASTM F876-13, indicating it exceeds ASTM F876 chlorine-resistance requirements for continuous-recirculation systems operating up to 140°F while also affording a 3-months UV-resistance level.

Uponor AquaPEX Tubing Coil — White



Part No.	Part Description	Coils/Pallet	List Price/Ea.
F1040250	¼" Uponor AquaPEX White, 100-ft. coil	50	
F1090375	⅜" Uponor AquaPEX White, 400-ft. coil	18	
F1120375	⅜" Uponor AquaPEX White, 1,000-ft. coil	12	
F1040500	½" Uponor AquaPEX White, 100-ft. coil	22	
F1060500	½" Uponor AquaPEX White, 300-ft. coil	18	
F1100500	½" Uponor AquaPEX White, 500-ft. coil	12	
F1120500	½" Uponor AquaPEX White, 1,000-ft. coil	8	
F1040750	¾" Uponor AquaPEX White, 100-ft. coil	11	
F1060750	¾" Uponor AquaPEX White, 300-ft. coil	12	
F1100750	¾" Uponor AquaPEX White, 500-ft. coil	8	
F1041000	1" Uponor AquaPEX White, 100-ft. coil	12	
F1061000	1" Uponor AquaPEX White, 300-ft. coil	5	
F1101000	1" Uponor AquaPEX White, 500-ft. coil	6	
F1061250	1¼" Uponor AquaPEX White, 100-ft. coil	7	
F1021250	1¼" Uponor AquaPEX White, 300-ft. coil	2	
F1061500	1½" Uponor AquaPEX White, 100-ft. coil	7	
F1021500	1½" Uponor AquaPEX White, 300-ft. coil	2	
F1062000	2" Uponor AquaPEX White, 100-ft. coil	5	
F1052000	2" Uponor AquaPEX White, 200-ft. coil	3	
F1022000	2" Uponor AquaPEX White, 300-ft. coil	2	
F1063000	3" Uponor AquaPEX White, 100-ft. coil	1	
F1023000	3" Uponor AquaPEX White, 350-ft. coil	1	

Note: 3" Uponor AquaPEX tubing uses WIPEX™ fittings (see page 111 for a listing of WIPEX fittings).