

# PMAX-0321



Heavy Duty Wall Mount for Outdoor Domes (for A8x, except A88)

## ► Specifications

### Device


Product Type	Camera Mount
Application Environment	Outdoor
Description	Heavy Duty Wall Mount for Outdoor Domes (for A8x, except A88)

### General

Weight	946g (2.09lb)
Dimensions	(W x H x D): 207mm x 160mm x 140mm (8.15" x 2.30" x 5.51")
Color	White
Material	Aluminum
Warranty	1 Year(s)

## ► Related Products

### Dome - Zoom Dome

A815		3MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8 (HOV:90.6°-32.7°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO
------	---	--

A817		8MP Video Analytics Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.3, Auto Focus (for installation), H.265/H.264, 4K/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, , , DI/DO, Built-in Analytics
A82		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 2.8x Zoom lens, f3.6-10mm/F1.5-2.8 (HOV:79.5°-38.1°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/60fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO
A83		2MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8 (HOV:88°-25°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO
A85		2MP Video Analytics Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, ELLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO, Built-in Analytics
A86		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Extreme WDR, SLLS, 5x Zoom lens, f2.7-13.5mm, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO
A87		5MP Outdoor Zoom Dome with D/N, Adaptive IR, Advanced WDR, SLLS, 4.3x Zoom lens, f2.8-12mm/F1.4-2.8 (HOV:71°-25°), P-Iris, Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP66, IK10, DI/DO
Z83		2MP Outdoor Zoom Dome with D/N, Adaptive IR, Superior WDR, SLLS, 4.3x Zoom lens, f2.8-12mm (HOV:112.7°-28.1°), Auto Focus (for installation), H.265/H.264, 1080p/30fps, 2D+3D DNR, MicroSDHC/MicroSDXC, PoE/DC12V, IP67, IK10
Z84		4MP Outdoor Zoom Dome with D/N, Adaptive IR, Superior WDR, SLLS, 4.3x Zoom lens, f2.8-12mm (HOV:91°-27°), Auto Focus (for installation), H.265/H.264, 2D+3D DNR, MicroSDHC/MicroSDXC, PoE/DC12V, IP67, IK10