

# PMAX-0330



Tilted Wall Mount for Outdoor Hemispheric Cameras

## ► Specifications

### Device






Product Type	Camera Mount
Application Environment	Indoor/Outdoor
Description	Tilted Wall Mount for Outdoor Hemispheric Cameras

### General

Weight	208.5g (0.46lb)
Dimensions	(Ø x H): 150mm x 34mm (5.91" x 1.34")
Color	Warm Gray
Material	Aluminum
Warranty	1 Year(s)
Tilted Angle	10°

## ▶ Related Products

### Dome - Hemispheric Dome

B74A		8MP Video Analytics Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10, DI/DO, Built-in Analytics
B76		12MP Video Analytics Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.3mm/F2.6 (HOV:194.22° (overview area), 118.5° (high detail area)), H.264, Dewarping, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10, DI/DO, Built-in Analytics
B76A		12MP Video Analytics Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.264, Dewarping, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10, DI/DO, Built-in Analytics
B78		12MP Video Analytics Outdoor Hemispheric Dome with D/N, Adaptive IR, Extreme WDR, SLLS, Fixed lens, f1.65mm/F2.8 (HOV:198.5° (overview area), 121.1° (high detail area)), H.265/H.264, Dewarping, 2D+3D DNR, Built-in Microphone, MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10, DI/DO, Built-in Analytics
I71		5MP Outdoor Hemispheric Dome with D/N, Advanced WDR, SLLS, Fixed lens, f1.05mm/F2.8 (HOV:189.7° (overview area), 115.7° (high detail area)), H.264, Dewarping, 2D+3D DNR, Audio, MicroSDHC/MicroSDXC, PoE/DC12V, IP68, IK10, DI/DO