

Fig. CT-121

Copper Tubing Riser Clamp

Size Range: 1/2" through 4"

Material: Carbon steel

Finish: Copper plated

Service: Recommended for support and steadying of copper tube risers, either insulated or non-insulated. This product is not intended for use with hanger rods.

Approvals: Complies with Federal Specification A-A-1192A (Type 8), WW-H-171-E (Type 8), ANSI/MSS SP-69 and MSS SP-58 (Type 8).

Service: For support and steadying of copper tubing risers.

Installation: Clamp is fitted and bolted preferably below a coupling or fitting on the tubing. Do not over tighten bolts.

Features: Rounded ears provide greater safety for personnel.

Ordering: Specify tube size, figure number, and name.




FIG. CT-121: LOADS (LBS) • WEIGHT (LBS) • DIMENSIONS (IN) • TORQUE (FT-LBS)

Tube Size	Max Load	Weight	L	G Width	Bolt Size	Torque Values
1/2	75	0.52	6 1/2	1	5/16	11
3/4		0.56	7			
1	120	0.94	9 3/8	1 1/4	3/8	21
1 1/4		0.98	9 5/8			
1 1/2	1.50	10				
2	1.50	10 3/8				
2 1/2	300	1.70	11 13/16			
3		1.80	11 1/2			
3 1/2		1.90	12			
4		2.60	13	1	1/2	46

Note: Minimum loads per MSS SP only applicable to 1 1/4" and up.

PROJECT INFORMATION		APPROVAL STAMP	
Project:		<input type="checkbox"/> Approved	
Address:		<input type="checkbox"/> Approved as noted	
Contractor:		<input type="checkbox"/> Not approved	
Engineer:		Remarks:	
Submittal Date:			
Notes 1:			
Notes 2:			