

HUBBELL
Wiring Device-Kellems

**Locking Devices, Hubbellock,
Industrial, Steel Shroud, Male Plug,
30A 600V AC, 20A 250V DC, 4-
Pole 5-Wire Grounding, Non NEMA,
Screw Terminal/White**

By Hubbell Wiring Device-Kellems
Catalog # [HBL25415B](#)

Locking Devices, Hubbellock®, Industrial, Steel Shroud, Male
Plug, 30A 600V AC, 20A 250V DC, 4-Pole 5-Wire Grounding
Hubbellock® Plug, Black nylon housing, Thermoset interior, Non
NEMA, Screw Terminal, Black/White



General

| | |
|-----------------------|--|
| Catalog Number | HBL25415B |
| Color | |
| Cord Range | 0.760"-1.200" (19.30-30.4) |
| EU RoHS Indicator | Contact Manufacturer |
| Item Type | 20A/30A Hubbellock® Plug |
| Material | Nylon |
| Number Of Poles | 4-Pole |
| Operating Temperature | Maximum continuous 75°C and minimum -40°C without Impact |
| Performance | Electrical - Current Interrupting - Certified for current interrupting at full rated current Electrical - Dielectric Voltage Withstand - 2,000V minimum Environmental - Flammability - UL 94 VO for Receptacles and Inlets. HB or better for Plugs and Connectors Environmental - Moisture Resistance - IP30 Suitability Environmental - Operating Temperatures - Maximum Continuous 75°C, Minimum -40°C (w/o impact) Mechanical - Terminal Accommodation - #10 AWG - #6 AWG stranded copper wire only. Mechanical - Terminal Identification - Terminals identified in accordance with UL 498 |
| Type | Plugs |
| UPC | 783585017488 |

Dimensions

| | |
|------------|---------------------------|
| Dimensions | 2.5 in x 2.5 in x 6.56 in |
| Height | 6.56 in |
| Length | 2.5 in |
| Weight | 1.4 lb |
| Width | 2.5 in |

Electrical Ratings

| | |
|----------------------------|---------------------------|
| Amperage Rating | 20/30 A |
| Current / Amperage Rating | 20/30 A |
| Dielectric Strength | Withstands 2,000V minimum |
| Voltage Rating | 250 VDC/600 VAC |
| Voltage Rating Description | 250 VDC/600 VAC |

Conductor Related

| | |
|-----------------|-------------------|
| Cable Range | 0.700 - 1.200 in |
| Number Of Wires | 5-Wire |
| Wire Size | #10 AWG to #6 AWG |

Certifications And Compliance

| | |
|----------------------|--|
| Industry Standard(s) | Certified to CSA Standard Listed to UL Standard |
|----------------------|--|

Logistics

| | |
|-----------------|-----|
| Carton Quantity | 10 |
| Pallet Quantity | 910 |

Product Assets

[Catalogs - WDK Catalog Full 2024](#)

[Warranty - Industrial & Commercial Products](#)



A Hubbell brand

©2024 Hubbell Incorporated. All rights reserved
WDK_MX-HBL25415B-SPEC-EN | REV 6/2024