



HUSKY SD 4000 COUPLINGS

Husky SD 4000 Couplings have been engineered by Anaco to provide a heavy-duty, all stainless steel coupling, balancing the desire for a more rigid joint with the need to provide a superior positive seal, which can accommodate possible disparities in the No-Hub pipe and fittings. This has been accomplished by manufacturing our coupling with a super-duty corrugated shield of sufficient width to accommodate additional surface-bearing sealing clamps.

CERTIFICATIONS & STANDARDS

- Meets ASTM C 1540
- Meets ASTM C 564
- Meets FM 1680 Class 1
- Meets CSA B 602
- IAPMO File 6726
- 100% made in the USA
- Compliant to BAA, TAA, ARRA and NAFTA

PRODUCTS

- Husky SD 4000
- Husky SD Transition 4200
 - PVC x CI 1½"–10"
- Husky SD Reducer
 - 2" x 1½", 3" x 2", 4" x 3", 4" x 2"
- Husky SD Transition 4100
 - CI x Copper 2" x 1½", 2" x 2"
- Husky SD 7000
 - 316 S.S. 1½"–10"

Size	Width	# Straps	Torque
1½" to 4"	3.0	4	80
5" & 6"	4.0	6	80
8" & 10"	4.0	6	80
12" & 15"	5.5	6	80

APPLICATIONS

- | | | |
|--------------|----------------|----------------------|
| ■ HOSPITALS | ■ MUNICIPAL | ■ SPORTS STADIUMS |
| ■ EDUCATION | ■ GOVERNMENT | ■ OFFICE/COMMERCIAL |
| ■ INDUSTRIAL | ■ CORRECTIONAL | ■ CONVENTION CENTERS |