




T8 Medium Bipin (1" diameter)



T8 Single Pin (1" diameter)

OCTRON® ECOLOGIC® T8 FLUORESCENT LAMPS (cont.)

OCTRON VIVID VALUE ECOLOGIC Lamps; Vivid Color: High CRI for color critical applications

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/ start IS (hrs)	Average Rated Life @12hrs/ start IS (hrs)	Average Rated Life @3hrs/ start PRS (hrs)	Average Rated Life @12hrs/ start PRS (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
32	T8	48	47.78	Med Bipin	22437	F032/V35/ECO	30	18000	22500	22500	27000	3500K	90	2450 (2250)	3,12,13,17,19
					22438	F032/V41/ECO	30	18000	22500	22500	27000	4100K	90	2450 (2250)	3,12,13,17,19
					22439	F032/V50/ECO	30	18000	22500	22500	27000	5000K	90	2450 (2250)	3,12,13,17,19
					22440	F032/V65/ECO	30	18000	22500	22500	27000	6500K	90	2400 (2210)	3,12,13,17,19

OCTRON 800 XP® 8-Foot SUPERSAVER® ECOLOGIC Lamps

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @ 3hrs/start IS (hrs)	Average Rated Life @ 12hrs/start IS (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
54	T8	96	94.00	Single Pin	22100	F096/54W/835/XP/SS/ECO3	24	24000	36000	3500	85	5700 (5360)	3,5,12,13,17
					22101	F096/54W/841/XP/SS/ECO3	24	24000	36000	4100	85	5700 (5360)	3,5,12,13,17
					22347	F096/54W/850/XP/SS/ECO3	24	24000	36000	5000	85	5700 (5360)	3,5,12,13,17
50	T8	96	94.00	Single Pin	22421	F096/50W/841/XP/SS/ECO3	24	24000	36000	4100	85	5400 (5075)	3,5,12,13,17

OCTRON 800 XP 4, 6, and 8-Foot ECOLOGIC Lamps

Nominal Wattage	Bulb Shape	Nom. Length (in)	MOL (in)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @ 3hrs/start IS (hrs)	Average Rated Life @ 12hrs/start IS (hrs)	CCT (K)	CRI	Lumens Initial (Mean) at 25°C/77°F	Notes
28	T8	48	46.00	Single Pin	21599	F048/835/XP/ECO	24	24000	36000	3500	85	2850 (2680)	3,12,13,17
44	T8	72	70.00	Single Pin	21598	F072/835/XP/ECO	24	24000	36000	3500	85	4650 (4370)	3,12,13,17
59	T8	96	94.00	Single Pin	22036	F096/830/XP/ECO	24	24000	36000	3000	85	6100 (5730)	3,12,13,17
					22034	F096/835/XP/ECO	24	24000	36000	3500	85	6100 (5730)	3,12,13,17
					22032	F096/841/XP/ECO	24	24000	36000	4100	85	6100 (5730)	3,12,13,17
					22174	F096/850/XP/ECO	24	24000	36000	5000	85	6100 (5730)	3,12,13,17