

Industrial Connector Housings (ICH) Holds 2 CCH connector panels, black



**Part Number:
ICH-02P**

Corning industrial connector housing (ICH) family is ideal for manufacturing and industrial applications. The ICH has a tough, baked-on black powder-coated finish, and they are IEC IP64 and NEMA 3S tested. The housings are designed to accommodate conduit with concentric knockouts and accept standard CCH connector panels and modules. Splicing is accomplished with the splice tray holding kit that may be ordered separately. The units have a padlock outer door and a separate inner door to protect the provider side of the unit from unauthorized access. The inner door may also be locked by using an optional key lock.

The ICH (ICH-02P, ICH-06P and ICH-12P) is IEC IP64 and NEMA 3S tested with a tough, baked-on, smooth black powder-coated finish.

Features and Benefits

IP tested

Reliability in harsh environments

Routing guides, cable strain-relief provisions included

Easy, out-of-the-box installation

Keyhole mounting holes

Fast installation



Industrial Connector Housing (ICH), holds two CCH connector panels, black

Industrial Connector Housings (ICH) Holds 2 CCH connector panels, black



Specifications

General Specifications	
Product Type	Wall-Mountable Hardware
Mounting Type	Wall-Mountable
Application	Enterprise Networks

Standards	
RoHS	Free of hazardous substances according to RoHS 2011/65/EU

Design	
Housing Type	ICH
Number of Panels per Housing	2
Panel or Module Type	CCH
Splice Tray Options	Up to 4 category 2R or 2 category 4R splice trays

Design - Adapter	
Housing Color	Black

Dimensions	
Height	267 mm (10.51 in)
Depth	140 mm (5.51 in)

Ordering Information	
Product Number	ICH-02P
EAN Code	4056418200101

Industrial Connector Housings (ICH) Holds 2 CCH connector panels, black



Ordering Information	
Package Contents	"Housing; installation guide; 2 blank panels; unit ID label; UCC strain-relief kit; UCC strain-relief bracket; central strength member strain-relief kit; 2 self-locking nuts, 6-32 SS; 18 1/8 x 4-in tie wraps"
Shipping Weight	4.5 kg
Width	330 mm (12.99 in)
Units per Delivery	1/1



Corning Optical Communications LLC • 4200 Corning Place • Charlotte, NC • 28216 • United States
800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified. © 2023 Corning Optical Communications. All rights reserved.