

30 368

## GROHE ZEDRA

### SINGLE-HANDLE PULL DOWN TRIPLE SPRAY BAR FAUCET 1.75 GPM

Pure Freude  
an Wasser



#### STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- Speed Clean® anti-lime system
- 15 1/4" Faucet height
- 8 3/8" Aerator height
- 7 15/16" Faucet reach
- For bar sinks
- Pull-down spray with 3 spray types: laminar spray, shower spray, and blade spray (reduced water consumption by up to 50% and even stronger spray performance)
- Stop function - pause button to stop the water flow
- Automatic return to laminar spray
- Adjustable flow rate limiter
- 360° Swivel spout
- Nylon braided flex hoses
- 1.75gpm
- Compatible with GROHE Foot Control retro-fit set (30 310 000)
- GROHE Zedra is the new name for Ladylux L2



#### PRODUCT FEATURES:



-  GROHE SilkMove®
-  GROHE StarLight®
-  GROHE QuickFix®

#### CERTIFICATIONS:



- ADA
- CEC Certified
- Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- CSA B125.1
- ASME A112.18.1
- Complies with lead plumbing laws

#### AVAILABLE FINISHES:

- 30368002**  GROHE StarLight® Chrome
- 303682432**  Matte Black
- 30368DC2**  SuperSteel InfinityFinish™
- 30368GN2**  Brushed Cool Sunrise

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.

We reserve the right to make revisions without notice to product specifications. 04-05-2023

**US**  
Tel: 1.630.582.7711 Fax: 1.630.582.7722  
For the most current Specification Sheet,  
go to [www.grohe.us](http://www.grohe.us).

**Canada**  
Tel: 1.888.644.7643 Fax: 1.905.366.2071  
For the most current Specification Sheet,  
go to [www.grohe.ca](http://www.grohe.ca).

PART OF **LIXIL**

30 368

# GROHE ZEDRA

## SINGLE-HANDLE PULL DOWN TRIPLE SPRAY BAR FAUCET 1.75 GPM

Pure Freude  
an Wasser



### TECHNICAL DATA:

Product Height	15-1/4 in
Product Length	9 in
Product Width	6-5/16 in
Fitting Spout Height	8-3/8 in
Fitting Spout Reach	7-15/16 in
GPM (Min)-GPM (Max)	1.75 gal (US)/min
Fitting No of Holes Required	1

