

No Flapper. No Leaks. No Problem.

The canister flush valve harnesses the force of gravity to send 360 degrees of water rushing into the system—increasing the power and effectiveness of the flush

Three-Bolt Installation

Three encapsulated pre-installed bolts save installation time and provide more options for adjustment

Ideal Retrofit Footprint

Great for remodeling, the toilet base is large enough to cover most existing toilet footprints

Dual-Flush


Dual-flush models feature an innovative trip lever that combines water savings with a powerful flush by offering the choice of 1.1 or 1.6 gallons per flush

Easy to Clean

The one-piece design, concealed trapway and Clean Caps®—our low-profile toilet floor bolt caps—make it easy to keep the toilet clean (available exclusively on K-76301)

Comfort Height® Bowl

All Highline toilets feature a taller bowl height which makes sitting and standing easier



THREE-BOLT INSTALLATION



DUAL-FLUSH



CLEAN CAPS

HIGHLINE

SKU	Tank SKU	Bowl SKU	Bowl Shape	Rough-In	GPF	ADA	Right-Hand Trip Lever Option	Insuliner* Option	Additional Features
K-5298	K-5308	K-5297	Elongated	12"	1.0	•	•		
K-3989	K-4458	K-4199	Elongated	12"	1.1 / 1.6	•	•		
K-76301	K-5311	K-80020	Elongated	12"	1.28	•	•		Concealed Trapway, Clean Caps
K-3999	K-4467	K-4199	Elongated	12"	1.28	•	•	•	
K-5481	K-4467	K-5393	Round-Front	12"	1.28	•	•		
K-3979	K-4468	K-4199	Elongated	12"	1.6	•	•		
K-3949	K-4841	K-4199	Elongated	14"	1.28	•	•	•	
K-6393	K-4458	K-4373	Elongated	10"	1.1 / 1.6	•	•		
K-3889	K-4467	K-4373	Elongated	10"	1.28	•	•	•	

To learn more about WaterSense®-labeled toilets, visit EPA.gov/WaterSense.

*Insuliner® tank liner minimizes condensation on the tank when exposed to high humidity.