


COMPACT FLUORESCENT LAMPS


The overall length of DULUX® compact fluorescent lamps is measured from the bottom of the base to the outside edge of the glass. In many cases, the bottom of the base is the bottom of the center post of the base of the lamp.




DULUX S



DULUX S/E




DULUX D




DULUX D/E




DULUX T



DULUX T/E
DULUX T/E/IN



DULUX L




DULUX F

BASES


Pin-based compact fluorescent lamps have either 2 pins or 4 pins. Each 2-pin lamp has an internal starter and is designed for preheat, magnetic operation. The 4-pin lamps are designed for electronic ballast operation and are dimmable. These lamps have no internal starter; starting the lamps is a function of the ballast.

Medium screw base, compact fluorescent lamps have integral ballasts.

FOR CHOKE/STARTER OPERATION



FOR ELECTRONIC OR DIMMING OPERATION



LAMP DISPOSAL LABELING

The following information appears on the packages of fluorescent lamps.



For weight and measurement information, please visit www.sylvania.com



DULUX T/E

Compact Fluorescent Lamps (cont.)

DULUX® T/E/IN Amalgam 4-Pin Extended Life SUPERSAVER® ECOLOGIC® Triple-Tube Compact Fluorescent Lamps – For Dimming and Electronic Ballast

Nominal Wattage	Bulb Shape	MOL (in)	MOL (mm)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life @3hrs/start (hrs)	Average Rated Life @12hrs/start (hrs)	CCT (K)	CRI	Approx. Lumens Initial (Mean) at 25°C/77°F	Approx. Lumens Initial (Mean) at 30°C/86°F	Notes
21	T (T4)	4.96	126	GX24Q-3	21100	CF26DT/E/IN/21W/830/XL/SS/ECO	50	26000	30000	3000	82	1470 (1260)	1500 (1290)	☞, 1, 2, 4, 5, 9, 10
					21101	CF26DT/E/IN/21W/835/XL/SS/ECO	50	26000	30000	3500	82	1470 (1260)	1500 (1290)	☞, 1, 2, 4, 5, 9, 10
					21102	CF26DT/E/IN/21W/841/XL/SS/ECO	50	26000	30000	4100	82	1470 (1260)	1500 (1290)	☞, 1, 2, 4, 5, 9, 10
28	T (T4)	5.6	142	GX24Q-3	21106	CF32DT/E/IN/28W/830/XL/SS/ECO	50	26000	30000	3000	82	1960 (1690)	2000 (1720)	☞, 1, 2, 4, 5, 9, 10
					21107	CF32DT/E/IN/28W/835/XL/SS/ECO	50	26000	30000	3500	82	1960 (1690)	2000 (1720)	☞, 1, 2, 4, 5, 9, 10
					21108	CF32DT/E/IN/28W/841/XL/SS/ECO	50	26000	30000	4100	82	1960 (1690)	2000 (1720)	☞, 1, 2, 4, 5, 9, 10
38	T (T4)	6.5	163	GX24Q-4	21103	CF42DT/E/IN/38W/830/XL/SS/ECO	50	26000	30000	3000	82	2600 (2235)	2650 (2280)	☞, 1, 2, 4, 5, 9, 10
					21104	CF42DT/E/IN/38W/835/XL/SS/ECO	50	26000	30000	3500	82	2600 (2235)	2650 (2280)	☞, 1, 2, 4, 5, 9, 10
					21105	CF42DT/E/IN/38W/841/XL/SS/ECO	50	26000	30000	4100	82	2600 (2235)	2650 (2280)	☞, 1, 2, 4, 5, 9, 10

DULUX T/E/IN Amalgam 4-Pin ECOLOGIC Triple-Tube Compact Fluorescent Lamps – For Dimming and Electronic Ballast

Nominal Wattage	Bulb Shape	MOL (in)	MOL (mm)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life (hrs)	CCT (K)	CRI	Approx. Lumens Initial (Mean) at 25°C/77°F	Approx. Lumens Initial (Mean) at 30°C/86°F	Notes
18	T (T4)	4.4	111	GX24Q-2	20875	CF18DT/E/IN/827/ECO	50	12000	2700	82	1165 (1000)	1200 (1030)	☞, 1, 2, 4, 5, 9, 10
					20876	CF18DT/E/IN/830/ECO	50	12000	3000	82	1165 (1000)	1200 (1030)	☞, 1, 2, 4, 5, 9, 10
					20877	CF18DT/E/IN/835/ECO	50	12000	3500	82	1165 (1000)	1200 (1030)	☞, 1, 2, 4, 5, 9, 10
					20878	CF18DT/E/IN/841/ECO	50	12000	4100	82	1165 (1000)	1200 (1030)	☞, 1, 2, 4, 5, 9, 10
26	T (T4)	5	126	GX24Q-3	20879	CF26DT/E/IN/827/ECO	50	16000	2700	82	1745 (1500)	1800 (1550)	☞, 1, 2, 4, 5, 9, 10
					20880	CF26DT/E/IN/830/ECO	50	16000	3000	82	1745 (1500)	1800 (1550)	☞, 1, 2, 4, 5, 9, 10
					20881	CF26DT/E/IN/835/ECO	50	16000	3500	82	1745 (1500)	1800 (1550)	☞, 1, 2, 4, 5, 9, 10
					20882	CF26DT/E/IN/841/ECO	50	16000	4100	82	1745 (1500)	1800 (1550)	☞, 1, 2, 4, 5, 9, 10
32	T (T4)	5.6	142	GX24Q-3	20883	CF32DT/E/IN/827/ECO	50	16000	2700	82	2330 (2000)	2400 (2065)	☞, 1, 2, 4, 5, 9, 10
					20884	CF32DT/E/IN/830/ECO	50	16000	3000	82	2330 (2000)	2400 (2065)	☞, 1, 2, 4, 5, 9, 10
					20885	CF32DT/E/IN/835/ECO	50	16000	3500	82	2330 (2000)	2400 (2065)	☞, 1, 2, 4, 5, 9, 10
					20886	CF32DT/E/IN/841/ECO	50	16000	4100	82	2330 (2000)	2400 (2065)	☞, 1, 2, 4, 5, 9, 10
42	T (T4)	6.5	163	GX24Q-4	20887	CF42DT/E/IN/827/ECO	50	16000	2700	82	3105 (2670)	3200 (2750)	☞, 1, 2, 4, 5, 9, 10
					20888	CF42DT/E/IN/830/ECO	50	16000	3000	82	3105 (2670)	3200 (2750)	☞, 1, 2, 4, 5, 9, 10
					20871	CF42DT/E/IN/835/ECO	50	16000	3500	82	3105 (2670)	3200 (2750)	☞, 1, 2, 4, 5, 9, 10
					20890	CF42DT/E/IN/841/ECO	50	16000	4100	82	3105 (2670)	3200 (2750)	☞, 1, 2, 4, 5, 9, 10

DULUX T/E 4-Pin ECOLOGIC Triple-Tube Compact Fluorescent Lamps – For Dimming and Electronic Ballast

Nominal Wattage	Bulb Shape	MOL (in)	MOL (mm)	Base	Product Number	Ordering Abbreviation	Pkg Qty	Average Rated Life (hrs)	CCT (K)	CRI	Approx. Lumens Initial (Mean) at 25°C/77°F	Notes
13	T (T4)	4.2	126	GX24Q-1	20891	CF13DT/E/827/ECO	50	12000	2700	82	900 (775)	☞, 1, 2, 4, 5, 9
					20892	CF13DT/E/830/ECO	50	12000	3000	82	900 (775)	☞, 1, 2, 4, 5, 9
					20893	CF13DT/E/835/ECO	50	12000	3500	82	900 (775)	☞, 1, 2, 4, 5, 9
					20894	CF13DT/E/841/ECO	50	12000	4100	82	900 (775)	☞, 1, 2, 4, 5, 9
26	T (T4)	5.6	142	GX24Q-3	20767	CF26DT/E/827/ECO	50	12000	2700	82	1800 (1550)	☞, 1, 2, 4, 5, 9

For the current listing of available products and more complete product information, please visit us at www.sylvania.com.

Specifications subject to change without notice.