

6" Recessed

Sloped Ceiling Housings

For complete fixture, order housing with trim.



New Construction IC
with E26 socket

P645-TG

Ceiling opening: 6-7/8"
Plaster frame: 8-3/8" x 13"
Recessed depth: 7-5/8"
Pryouts: 1/2" and 3/4"

P645-TG HOUSING FEATURES

- Maintains lamp in a vertical position from a 0° to a 45° slope (0/12 to 12/12 pitch).
- UL and CUL listed for damp locations and through wiring.
- Can be installed in ceiling from 1/2" to 1-1/2".
- Locking screw to secure housing in place.
- Integral nailer and T-bar clamps.
- Bar hangers, with nail grip feature, span to position housing anywhere within 24" joist spacing.
- Rated for 8 #12 90° conductors (4 in/4 out).
- Integral Romex clamps.
- Easy spring installation of trims.



New Construction Air-Tight & IC
with E26 socket

P645-AT

Ceiling opening: 6-7/8"
Plaster frame: 8-3/8" x 13"
Recessed depth: 7-5/8"
Pryouts: 1/2" and 3/4"

P645-AT HOUSING FEATURES

- Maintains lamp in a vertical position from a 0° to a 45° slope (0/12 to 12/12 pitch).
- UL and CUL listed for damp locations and through wiring.
- Meets Washington State Energy Code requirements.
- Can be installed in ceiling from 1/2" to 1-1/2".
- Locking screw to secure housing in place.
- Integral nailer and T-bar clamps.
- Bar hangers, with nail grip feature, span to position housing anywhere within 24" joist spacing.
- Rated for 8 #12 90° conductors (4 in/4 out).
- Integral Romex clamps.



Remodel IC with E26 socket

P745-IC

Ceiling opening: 7-3/8"
Recessed depth: 7-1/4"
Pryouts: 1/2"

P745-IC HOUSING FEATURES

- Maintains lamp in a vertical position from a 0° to a 45° slope (0/12 to 12/12 pitch).
- UL and CUL listed for damp locations and through wiring.
- Can be installed in ceiling from 1/2" to 1-1/4".
- Easy spring installation of trims.
- Slide bars stay in place, and have locking screw to secure housing in place.
- Integral nailer and T-bar clamps.
- Bar hangers, with nail grip feature, span to position housing anywhere within 24" joist spacing.
- Rated for 4 #12 90° conductors (2 in/2 out).
- Integral Romex clamps.

Trims

8-1/4" outside diameter.



BAFFLE

P8004-20 Antique Bronze

P645-TG 75w BR30, 75w BR30/PAR30LN

P645-AT 75w BR30, 75w PAR30LN



BAFFLE

P8004-28 White

P645-TG 75w BR30, 75w BR30/PAR30LN

P645-AT 75w BR30, 75w PAR30LN

P745-IC 65w BR30, 75w PAR30LN



BAFFLE

P8004-31 Black

P645-TG 75w BR30, 75w BR30/PAR30LN

P645-AT 75w BR30, 75w PAR30LN

P745-IC 65w BR30, 75w PAR30LN

Lamp wattages shown are maximum.
For accessories see page 795.