

6" Recessed

Shallow Housings

For complete fixture, order housing with trim.



New Construction IC and Non-IC with E26 socket

P86-TG

Ceiling opening: 6-7/8" dia.
Plaster frame: 7-7/8" x 10-3/4"
Recessed depth: 5-1/2"
Pryouts 1/2" and 3/4"

P86-TG HOUSING FEATURES

- Designed for shallow plenums and 2" x 6" construction.
- UL and CUL listed for damp locations and through wiring.
- Can be installed in ceilings from 1/2" to 1-1/2" thick.
- Integral nailer and T-bar mounting clamp.
- Integral bar hanger.
- Integral Romex clamp.
- Rated for 8 #12 90° conductors (4 in/4 out).

*P86-TG and P186-TG can be converted to Air-Tight in the field with P8593-01 Gasket Kit. See page 795.



Remodel IC and Non-IC with E26 socket

P186-TG

Ceiling opening: 6-5/8" dia.
Recessed depth: 5-1/2"
Pryouts 1/2"

P186-TG HOUSING FEATURES

- Retrofit version of P86-TG.
- UL and CUL listed for damp locations and through wiring.
- Exclusive locking bars permit quick mounting in ceilings 1/2" to 1" thick.
- Integral flange on housing.
- For use in existing ceilings.
- Rated for 4 #12 90° conductors (2 in/2 out).
- Rated for 60° supply wires in end-of-run applications.

Non-IC Trims

Insulation must be 3" from housing.
7-3/4" outside diameter.



P8020-28 White
Wet location listed.
Metal flange.
60w A19

IC Trims

For insulated ceilings. 7-3/4" outside diameter.
IC trims may be used as non-IC trims with same wattages.



STEP BAFFLE
P8063-28 White
P8063-31 Black
75w PAR30, 65w BR30



OPEN TRIM
P8073-28 White
75w PAR30 Long Neck,
65w BR30



EYEBALL
P6676-29 White
Rotates 358°,
tilts 30° max.
75w PAR30, 65w BR30



OPEN SHOWER TRIM
P8073WL-28 White
Wet location listed.
Metal flange.
50w PAR30*

LED IC Trims

- LED ROUND**
- P8071-09-30K** Brushed Nickel
 - P8071-20-30K** Antique Bronze
 - P8071-28-30K** White
 - P8071-31-30K** Black
- 10.5w integrated LED, 3000K, 90CRI, 725 lumens.



P8071-09-30K



P8071-20-30K



P8071-28-30K



P8071-31-30K

- LED EYEBALL**
- P8076-09-30K** Brushed Nickel
 - P8076-20-30K** Antique Bronze
 - P8076-28-30K** White
 - P8076-31-30K** Black
- 10.5w integrated LED, 3000K, 90CRI, 700 lumens.



P8076-09-30K



P8076-20-30K



P8076-28-30K



P8076-31-30K

All fixtures:

