


# Reducing Bushings

## Steel



### Features

- Rounded bushing protects conductor

### Applications

- Dry location use only
- Use to reduce the entry size of a run of threaded conduit

### Standard Material


- Steel

### Standard Finish

- Zinc plated

| Catalog Number | UPC   | Size                   | Ship Case | Weight/Case | A    | B     |
|----------------|-------|------------------------|-----------|-------------|------|-------|
| <b>RB1</b>     | 20060 | <b>1/2" x 3/8"</b>     | 100       | 2           | .563 | .75   |
| <b>RB2</b>     | 20070 | <b>3/4" x 1/2"</b>     | 100       | 4           | .65  | .92   |
| <b>RB3</b>     | 20080 | <b>1" x 1/2"</b>       | 50        | 6           | .715 | 1.125 |
| <b>RB4</b>     | 20090 | <b>1" x 3/4"</b>       | 50        | 7           | .715 | 1.125 |
| <b>RB5</b>     | 20100 | <b>1-1/4" x 1/2"</b>   | 25        | 7           | .82  | 1.47  |
| <b>RB6</b>     | 20110 | <b>1-1/4" x 3/4"</b>   | 25        | 8           | .82  | 1.47  |
| <b>RB7</b>     | 20120 | <b>1-1/4" x 1"</b>     | 25        | 4           | .82  | 1.47  |
| <b>RB8</b>     | 20130 | <b>1-1/2" x 1/2"</b>   | 25        | 11          | .85  | 1.70  |
| <b>RB9</b>     | 20140 | <b>1-1/2" x 3/4"</b>   | 25        | 8           | .85  | 1.70  |
| <b>RB10</b>    | 20150 | <b>1-1/2" x 1"</b>     | 25        | 7           | .85  | 1.70  |
| <b>RB11</b>    | 20160 | <b>1-1/2" x 1-1/4"</b> | 25        | 3           | .85  | 1.70  |
| <b>RB12</b>    | 20170 | <b>2" x 1/2"</b>       | 10        | 3           | .97  | 2.23  |
| <b>RB13</b>    | 20180 | <b>2" x 3/4"</b>       | 10        | 8           | .97  | 2.23  |
| <b>RB14</b>    | 20190 | <b>2" x 1"</b>         | 10        | 7           | .97  | 2.23  |
| <b>RB15</b>    | 20200 | <b>2" x 1-1/4"</b>     | 10        | 5           | .97  | 2.23  |
| <b>RB16</b>    | 20210 | <b>2" x 1-1/2"</b>     | 10        | 3           | .97  | 2.23  |

## Malleable Iron



### Features

- Rounded bushing protects conductor

### Applications

- Dry location use only
- Use to reduce the entry size of a run of threaded conduit

### Standard Material

- Malleable iron

### Standard Finish

- Zinc plated

| Catalog Number | UPC   | Size                   | Ship Case | Weight/Case | A    | B    |
|----------------|-------|------------------------|-----------|-------------|------|------|
| <b>RB17</b>    | 20220 | <b>2-1/2" x 1"</b>     | 10        | 11          | 1.3  | 2.88 |
| <b>RB18</b>    | 20230 | <b>2-1/2" x 1-1/4"</b> | 10        | 13          | 1.3  | 2.88 |
| <b>RB19</b>    | 20240 | <b>2-1/2" x 1-1/2"</b> | 10        | 9           | 1.3  | 2.88 |
| <b>RB20</b>    | 20250 | <b>2-1/2" x 2"</b>     | 10        | 6           | 1.3  | 2.88 |
| <b>RB21</b>    | 20260 | <b>3" x 1-1/4"</b>     | 10        | 18          | 1.54 | 3.5  |
| <b>RB22</b>    | 20270 | <b>3" x 1-1/2"</b>     | 10        | 17          | 1.54 | 3.5  |
| <b>RB23</b>    | 20280 | <b>3" x 2"</b>         | 10        | 16          | 1.54 | 3.5  |
| <b>RB24</b>    | 20290 | <b>3" x 2-1/2"</b>     | 10        | 10          | 1.54 | 3.5  |
| <b>RB25</b>    | 20300 | <b>3-1/2" x 1-1/2"</b> | 10        | 24          | 1.59 | 4    |
| <b>RB26</b>    | 20310 | <b>3-1/2" x 2"</b>     | 10        | 29          | 1.59 | 4    |
| <b>RB27</b>    | 20320 | <b>3-1/2" x 2-1/2"</b> | 10        | 25          | 1.59 | 4    |
| <b>RB28</b>    | 20330 | <b>3-1/2" x 3"</b>     | 10        | 11          | 1.59 | 4    |
| <b>RB29</b>    | 20340 | <b>4" x 2"</b>         | 10        | 28          | 1.77 | 4.51 |
| <b>RB30</b>    | 20350 | <b>4" x 2-1/2"</b>     | 10        | 27          | 1.77 | 4.51 |
| <b>RB31</b>    | 20360 | <b>4" x 3"</b>         | 10        | 22          | 1.77 | 4.51 |
| <b>RB32</b>    | 20370 | <b>4" x 3-1/2"</b>     | 10        | 16          | 1.77 | 4.51 |