

IMPROVED INDUSTRIAL SPRAYER!

Same Gelling Action...Better surface coverage



Reduces danger of fire to surrounding surfaces such as studs, drywall and insulation

- Helps prevent heat damage to components and surrounding materials during soldering, brazing and welding
- Saves time by eliminating the costly disassembly of valves and other components before soldering, brazing or welding
- Unique gelling formula sticks to surfaces, without dripping or running off
- Clear, non-staining gel leaves no residue, eliminating cleanup
- Safe, non-toxic, odorless and harmless to skin

REVENTS HEAT AND FIRE DAMAGE

Protective Uses:

- Protects the seals and seats in ball, dielectric and solenoid valves
- Protects finished surfaces from discoloration due to adjacent torch operations
- Protects soldered joints from loosening when soldering adjacent joints
- Prevents buckling or distortion of thin metal sheet during brazing or welding

$\boldsymbol{\cap}$		- DI	NCI	MFO	DAA		\sim	•
ш.	154 D	12:41	MLTI	NFO	1541//	AII		v

Part No.	Size	QTY/Case	Wt/Case	
11524	2 Fl. oz.	48	30 Lbs.	
11527	2 Fl. oz.	12	9.6 Lbs.	
11513	16 Fl. oz.	24	36 Lbs.	
11509	32 Fl. oz.	12	36 Lbs.	

Now Available in 2 oz. Bottles!

CONTACT

Ph: 847-956-7600 Fax: 847-956-9885 Customer Service: 847-956-3867 customer_service@laco.com coolgel@laco.com www.laco.com



Call, write or email for additional information

1201 Pratt Boulevard
Elk Grove Village, Illinois 60007-5746
1-800-621-4025 • 1-847-956-7600 • Fax: 1-800-448-5436
www.laco.com
Email: customer_service@laco.com

Family owned and operated since 1934