

## Small Wall Lantern

 Wall mounted • Wet location listed **PROGRESS LED**


### Description:

LED wall lantern with etched white linen glass. Includes dark sky shield for full cut-off illumination or remove for a traditional lighting effect. 120V AC replaceable LED module, 623 lumens (source), 3000K color temperature and 90+ CRI.

### Specifications:

- Black (-31) (powder coat paint)
- Aluminum Construction
- Etched White Linen glass cylindrical diffuser
- LED Module is replaceable (part # 93054049)
- Etched white linen glass.
- Includes removable dark sky shield for full cut-off illumination.
- Powder coated finish.
- 623 lumens 69.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

### Performance:

|                        |  |
|------------------------|--|
| Number of Modules      | 1  |
| Input Power            | 9w   |
| Input Voltage          | 120 V  |
| Input Frequency        | 60 Hz  |
| Lumens/LPW (Source)    | 623/69.2 (LM-82)   |
| Lumens/LPW (Delivered) | 130/17.1 (LM-79)   |
| CCT                    | 3000 K   |
| CRI                    | 90 CRI   |
| Life (hours)           | 60,000 (L70/TM-21)   |
| FCC                    | Meets FCC Title 47, Part 15 Class B  |
| Min. Start Temp        | -30 °C   |
| Max. Operating Temp    | 30 °C  |
| Warranty               | 5 year warranty  |
| Labels                 | cCSAus Wet location listed<br>ENERGY STAR® qualified<br>Meets California Title 24 high efficacy requirements<br>for outdoor use only |

## P6084-3130K9

### Images:



### Dimensions:

Width: 7"  
Depth: 8-5/8"  
Height: 10-3/8"  
H/CTR: 3-1/8"

Glass  
Width: 4-5/8"  
Height: 5-7/8"