




Z6000AV-ONE

1.1 gpf Exposed Manual Flush Valve with Top Spud Connection
for High Efficiency Water Closets



This product should be used with a WaterSense labeled counterpart with a compatible flush volume to ensure that the entire system meets the requirements for water efficiency and performance.

Suffix Options (Check/Specify Appropriate Options)

_____	-BG	BioCare Handle
_____	-H	Handle on Front of Flush Valve
_____	-L	1" [25] Metal Push Button
_____	-L3	3" [76] Metal Push Button
_____	-YJ	Split Ring Pipe Support
_____	-YK	Solid Ring Pipe Support
_____	-YO	Bumper on Angle Stop
_____		Other

ENGINEERING SPECIFICATION: ZURN Z6000AV-ONE AquaVantage® 'AV' Exposed Closet Flush Valve - Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with Zurn's 1.1 gpf AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant by-pass. The valve is ADA compliant with a non-hold open and no leak handle feature, high back pressure vacuum breaker, one piece hex coupling nut, adjustable tailpiece, spud coupling and flange for top spud connection. Control stop has internal siphon-guard protection, vandal resistant stop cap, sweat solder kit, and a cast wall flange with set screw. Internal seals are made of chloramine resistant materials.

This space is for Architectural/engineering Approval

The information contained in this document is subject to change without notice.
Please contact Zurn for most up to date information.

ZURN INDUSTRIES, LLC. ♦ COMMERCIAL BRASS OPERATION ♦ 5900 ELWIN BUCHANAN DRIVE ♦ SANFORD NC 27330

Phone: 1-800-997-3876 ♦ Fax: 919-775-3541 ♦ World Wide Web: www.zurn.com

In Canada: ZURN INDUSTRIES LIMITED ♦ 7900 Goreway Drive Unit 10 ♦ Brampton, Ontario L6T5W6 ♦ Phone: 905-405-8272 Fax: 905-405-1292